



## Split Mural Super DC Inverter

Ecodesign

U-Crown						
Modeli	GWH09UB-K3DNA4F		GWH12UB-K3DNA4F	GWH18UC-K3DNA4F		
Funksioni			Ftohje/Ngrohje	Ftohje/Ngrohje	Ftohje/Ngrohje	
Kapaciteti	Ftohje	Btu/h	9000(1300~13600)	1200(1300~15200)	18000(3071~19619)	
	Ngrohje	Btu/h	10200((1900~16400)	12300(1900~18400)	18000(2559~24737)	
Pdesignh(A)Pdesignh(W)Pdesignh©			Btu/h	9200/9600/9200	10200/11000/10200	17742/180832/21154
SEER/SCOP/(A)/SCOP(W)SCOP©			W/W	7.5/4.6/5.1/3.8	7.0/4.6/5.1/3.8	6.1/4.0/4.0/3.1
Klasa e energjise Ftohje/Ngr.(A)/Ngr.(W)Ngr.(C)				A++/A++/A+++/A	A++/A++/A+++/A	A++/A+/A+/B
Furnizimi me energji			Ph, V, Hz	1Ph, 220-240V, 50hz	1Ph, 220-240V, 50hz	1Ph, 220-240V, 50hz
Hyrja e energjise	Ftohje	W	600(95~1550)	920(95~1550)	1600(200~2050)	
	Ngrohje	W	800(100~16300)	970(100~1680)	1420(200~2400)	
Intensiteti i rrymes	Ftohje	A	6.5	6.8	9.1	
	Ngrohje	A	6.8	7.1	10.6	
Volumi i fryrjes se ajrit	Indoor	m³/h (SH/H/ML)	650/530/400	720/550/420	850/750/600	
<b>Njesia e brendshme</b>						
Niveli i presionit te zhurmes	Indoor	dB(A)(SH/H/ML)	56/50/46	57/51/47	58/54/48/	
Dimensionet e jashtme	LxGjxTh	mm	860X305X170	860x305x170	960x320x205	
Dimensionet e paketimit	LxGjxTh	mm	935X388X295	935x388x295	1043x403x333	
Pesha	Indoor	kg	14	14	17	
<b>Njesia e jashtme</b>						
Niveli i presionit te zhurmes	Outdoor	dB(A)	62	62	63	
Lidhja e tubit	Gaz	mm	ø12	ø9.52	ø12	
	Likuid	mm	ø6	ø6	ø6	
Dimensionet e jashtme	LxGjxTh	mm	899X596X378	899x596x378	955x700x396	
Dimensionet e paketimit	LxGjxTh	mm	948X645X420	948x645x420	1029x750x458	
Pesha	Outdoor	kg	48	48	56	