



Floor Standing DC Inverter

Crown				
Model		GVH24AF-K3DNA4A		GVH48AF-M3DNA4A
Function			Cooling/ Heating	Cooling/ Heating
Capacity	Cooling	Btu/h	24000(8500~28500)	42000(21000~46000)
	Heating	Btu/h	26500(5500~32000)	48000(22000~52000)
EER/ C.O.P		W/W	3.21/3.61	3.21/3.61
Power supply		Ph, V, Hz	1Ph, 220-240V, 50Hz	3Ph, 380~415V, 50Hz
Power input	Cooling	W	2191(800~3600)	3950(1800~5500)
	Heating	W	2180(5500~3600)	3900(1700~5500)
Rated current	Cooling	A	9.92	6.8
	Heating	A	9.87	7.3
Airflow volume	Indoor	m ³ /h	1100	1850
Indoor unit				
Sound pressure level	Indoor	dB(A)(SH/H/M/L)	44/40/37	47/44/42
Outline dimension	(WxHxD)	mm	540x1790x320	580x1865x400
Weight	Indoor	kg	52	65
Outdoor unit				
Sound pressure level	Outdoor	dB(A)(SH/H/M/L)	56	58
Piping connection	Gas	mm	ø16	ø19
	Liquid	mm	ø6	ø12
Outline dimension	(WxHxD)	mm	980x790x440	950x1250x412
Weight	Outdoor	kg	77	112