



Split mural Super DC Inverter  
Ecodesign

Hansol							
Modeli			GWH09TB-S3DNA1D	GWH12TB-S3DNA1D	GWH18TC-S3DNA1D	GWH24TD-S3DNA1D	
Funksioni			Ftohje/Ngrohje	Ftohje/Ngrohje	Ftohje/Ngrohje	Ftohje/Ngrohje	
Kapaciteti	Ftohje	Btu/h	8871	11942	18000	24000	
	Ngrohje	Btu/h	10236	13648	18420	24000	
Pdesignh(A)Pdesignh(W)Pdesignh(C)			Btu/h	9554/9554/13684	11992/11250/17060	18420/18420/18420	24000/24000/24000
SEER/SCOP/(A)/SCOP(W)SCOP©			W/W	8.5/5.1/6.1/4.0	8.0/4.7/5.6/3.7	8.4/4.0/4.8/3.2	6.2/4.0/4.6/2.9
Furnizimi me energji			Ph, V, Hz	1Ph, 220-240V, 50hz	1Ph, 220-240V, 50hz	1Ph, 220-240V, 50hz	1Ph, 220-240V, 50hz
Klasa e energjisë Ftohje/Ngr.(A)/Ngr.(W)Ngr.(W)				A+++/A+++/A+++/A+	A++/A++/A+++/A	A++/A+/A++/B	A++/A+/A++/B
Energjia ne hyrje	Ftohje	W	600	900	1514	2000	
	Ngrohje	W	650	1000	1450	1960	
Intensiteti i rrymes	Ftohje	A	4.9	6.5	13.7	14.2	
	Ngrohje	A	7.1	8.0	14.0	14.2	
Volumi i fryrjes se ajrit	Indoor	m³/h	650	750	950	1200	
<b>Njesia e brendshme</b>							
Niveli i presionit te zhurmes	Indoor	dB(A)(SH/H/ML)	43/36/32/28	43/36/32/28	60/56/54/52/50/48/46	85/62/58/58/54/52/49	
Dimensionet e jashtme	LxGjxTh	mm	866/292/209	866x292x209	1018x319x230	1176x326x264	
Dimensionet e paketimit	LxGjxTh	mm	945/297/377	945x297x377	1097x340x397	1258x414x364	
Pesha	Indoor	kg	13	13	17	21	
<b>Njesia e jashtme</b>							
Niveli i presionit te zhurmes	Outdoor	dB(A)	63	63	65	58	
Lidhja e tubit	Gaz	mm	ø9.52	ø9.52	ø16	ø16	
	Likuid	mm	ø6	ø6	ø6	ø6	
Dimensionet e jashtme	LxGjxTh	mm	899X596X378	899x596x378	955x700x396	960x790x427	
Dimensionet e paketimit	LxGjxTh	mm	948X645X420	948x645x420	1029x750x458	1083x488x855	
Pesha	Outdoor	kg	48	47	52	70	