



Kondicioner dollap DC Inverter

I-Crown II			
Modeli		GVH24AF-K3DNA4A	
Funksioni		Ftohje/Ngrohje	
Kapaciteti	Ftohje	Btu/h	24000(7300~30000)
	Ngrohje	Btu/h	32400(5800~34800)
EER/ C.O.P		W/W	8.5/4.6
Furnizimi me energji		Ph, V, Hz	1Ph, 220-240V, 50Hz
Energjia ne hyrje	Ftohje	W	2100(440~3200)
	Ngrohje	W	3100(380~3900)
Intensiteti i rrymes	Ftohje	A	14.2
	Ngrohje	A	14.2
Volumi i fryrjes se ajrit	Indoor	m ³ /h	1200
Njesia e brendshme			
Niveli i presionit te zhurmes	Indoor	dB(A)(SH/H/M/L)	46/43/36/33
Dimensionet e jashtme	LxGjxTh	mm	1844x462x395
Pesha	Indoor	kg	46
Njesia e jashtme			
Niveli i presionit te zhurmes	Outdoor	dB(A)(SH/H/M/L)	57
Lidhja e tubit	Gaz	mm	ø16
	Likuid	mm	ø6
Dimensionet e jashtme	LxGjxTh	mm	980x790x440
Pesha	Outdoor	kg	63