



Njesite Outdoor

GMV5 Home							
Modeli			GMV-S120WL/A-S	GMV-S140WL/A-S	GMV-S160WL/A-S	GMV-S224W/A-X	GMV-S280W/A-X
Kapaciteti	Ftohje	kW	12.1	14	16	22.4	28
	Ngrohje	kW	14	16.5	18.5	25	31.5
ECOP		kW/kW	/	/	/	7	7
Furnizimi me energji		PhV/Hz	220-240V~1Ph~50/60Hz	220-240V~1Ph~50/60Hz	220-240V~1Ph~50/60Hz	380-415V 3Ph~50/60Hz	380-415V 3Ph~50/60Hz
Volumi i ngarkeses se gazit		kg	5	5	5	10.5	11
Fuqia ne hyrje	Ftohje	kW	3.05	3.98	4.85	5.35	7.7
	Ngrohje	kW	3.3	4.1	4.67	5.8	7.6
	Ngrohje uji	kW	3.3	3.8	4.2	5	5.2
Volumi i fryrjes se ajrit		m ³ /h	6000	6300	6600.0	14000	14000
		CFM	3531	3708	3884	8239	8239
Niveli i presionit te zhurmes		d(B)A	55	56	58	57	58
Lidhja e tubit	Gaz	mm	ø15.9	ø15.9	ø19.05	ø19.05	ø22.2
	Likuid	mm	ø9.52	ø9.52	ø9.52	ø9.52	ø9.52
	Gaz (presion i larte)	mm	ø12.7	ø12.7	ø12.7	ø15.9	ø15.9
Dimensionet (LxGjxTh)	E jashtme	mm	900x340x1345	900x340x1345	900x340x1345	1340x765x1605	1340x765x1605
	Paketimi	mm	998x458x1515	998x458x1515	998x458x1515	1420x840x1775	1420x840x1775
Pesha		Kg	123	123	123	310	310