



### 1-Way Cassette Type

Modeli			GMV-ND22TD/A-T	GMV-ND28TD/A-T	GMV-ND36TD/A-T	GMV-ND45TD/A-T	GMV-ND50TS/A-T
Kapaciteti	Ftohje	Kw	2.2	2.8	3.6	4.5	5
	Ngrohje	Kw	2.5	3.2	4	5	5.6
Furnizimi me energji		V/Ph/Hz	220~240/1/50 & 208~230/1/60				
Konsumi i energjise		W	30	30	30	45	45
Volumi i fryrjes se ajrit		m³/h	600/500/450	600/500/450	600/500/450	830/600/500	830/600/500
		CFM	355/295/265	355/295/265	355/295/265	490/355/295	490/355/295
Rryma nominale	Ftohje	A	0.2	0.2	0.2	0.3	0.3
	Ngrohje	A	0.2	0.2	0.2	0.3	0.3
	Ngrohje uji	A	/	/	/	/	/
Niveli i presionit te zhurmes		dB(A)	36/32/28	36/32/28	36/32/28	40/35/30	40/35/30
Lidhja e tubit	Likuid	mm	ø6.35	ø6.35	ø6.35	ø6.35	ø6.35
	Gaz	mm	ø9.52	ø12.7	ø12.7	ø12.7	ø12.7
Tubi i shkarkimit	Dia. jashtem	mm	ø25	ø25	ø25	ø25	ø25
	Trashesia	mm	2.5	2.5	2.5	2.5	2.5
Trupi kryesor	Dimensionet (GJxThxL)	E jashtme	mm	987x385x178	987x385x178	987x385x178	987x385x178
		Paketimi	mm	1307x501x310	1307x501x310	1307x501x310	1307x501x310
	Pesha neto/ bruto		kg	20.0/27.0	20.0/27.0	20.0/27.0	21.0/28.5
Paneli	Dimensionet (GJxThxL)	E jashtme	mm	1200x460x55	1200x460x55	1200x460x55	1200x460x55
		Paketimi	mm	1265x536x118	1265x536x118	1265x536x118	1265x536x118
	Pesha neto/ bruto		kg	4.2/6.0	4.2/6.0	4.2/6.0	4.2/6.0
Ngarkesa	40' GP	set	138	138	138	138	138
	40'HQ	set	138	138	138	138	138