



4-Way Cassette

Model			GMV-Rh28T/Na-K	GMV-Th36T/Na-K	GMV-Rh45T/Na-K	GMV-Rh50T/Na-K	GMV-Rh56T/Na-K	GMV-Rh63T/Na-K	GMV-Rh71T/Na-K	GMV-Rh80T/Na-K	GMV-Rh90T/Na-K	GMV-Rh100T/Na-K	GMV-Rh112T/Na-K	GMV-Rh125T/Na-K	
Capacity	Cooling	Kw	2.8	3.6	4.5	5	5.6	6.3	7.1	8	9	10	11.2	12.5	
	Heating	Kw	3.2	4	5	5.6	6.3	7.1	8	8.8	10	11	12.5	13.5	
Power supply		V/Ph/Hz	1/220-240/50												
Power consumption		W	65	65	65	65	83	83	83	83	133	133	133	133	
Airflow volume		m³/h	680	680	680	680	1180	1180	1180	1180	1860	1860	1860	1860	
		CFM	400	400	400	400	694	694	694	694	1095	1095	1095	1095	
Sound pressure level		dB(A)	37/35/33	37/35/33	37/35/33	37/35/33	39/37/35	39/37/35	39/37/35	39/37/35	40/38/36	40/38/36	40/38/36	40/38/36	
Main body	Dimensions (WxDxH)	Outline	mm	840x840x190	840x840x190	840x840x190	840x840x190	840x840x240	840x840x240	840x840x240	840x840x240	840x840x320	840x840x320	840x840x320	840x840x320
		Package	mm	1103x963x272	1103x963x272	1103x963x272	1103x963x272	1103x963x325	1103x963x325	1103x963x325	1103x963x325	963x963x409	963x963x409	963x963x409	963x963x409
	Net weight/Gross weight	kg	25/23	25/23	25/23	25/23	30/38	30/38	30/38	30/38	38/46	38/46	38/46	38/46	
Panel	Dimensions (WxDxH)	Outline	mm	950x950x65	950x950x65	950x950x65	950x950x65	950x950x60	950x950x60	950x950x60	950x950x60	950x950x60	950x950x60	950x950x60	950x950x60
		Package	mm	1043x1028x130	1043x1028x130	1043x1028x130	1043x1028x130	1043x1028x130	1043x1028x130	1043x1028x130	1043x1028x130	1043x1028x130	1043x1028x130	1043x1028x130	1043x1028x130
	Net weight/Gross weight	kg	6.5/10	6.5/10	6.5/10	6.5/10	6.5/10	6.5/10	6.5/10	6.5/10	6.5/10	6.5/10	6.5/10	6.5/10	
Conecting pipe	Liquid	mm	3/8	1/2	1/2	1/2	5/8	5/8	5/8	5/8	5/8	5/8	5/8	5/8	
	Gas	mm	1/4	1/4	1/4	1/4	3/8	3/8	3/8	3/8	3/8	3/8	3/8	3/8	
Loading quantity	40' GP	set	112	112	112	112	100	100	100	100	88	88	88	88	
	40'HQ	set	124	124	124	124	114	114	114	114	90	90	90	90	