



Cassette Type R410 Dc Inverter

U-Match Inverter Kasete														
Modeli	Njesia e jashtme		GUHD12NK3FO	GUHD18NK3FO	GUHD24NK3FO	GUHD30NK3FO	GUHD36NK3FO	GUHD36NM3FO	GUHD42NK3FO	GUHD42NM3FO	GUHD48NK3FO	GUHD48NM3FO	GUHD60NM3FO	
	Njesia e brendshme		Kasete	Kasete	Kasete	Kasete	Kasete	Kasete	Kasete	Kasete	Kasete	Kasete	Kasete	
			GKH12K3FI	GKH18K3FI	GKH24K3FI	GKH30K3FI	GKH36K3FI	GKH36K3FI	GKH42K3FI	GKH42K3FI	GKH48K3FI	GKH48K3FI	GKH60K3FI	
Kapaciteti	Ftohje	W	3500	5000	7000	8300	1000	1000	11000	11000	14000	14000	16000	
		Btu/h	11942	17060	23884	28319.6	34120	34120	37532	37532	47768	47768	54592	
	Ngrohje	W	3800	5600	8000	9200	12000	12000	12500	12500	16000	16000	17000	
		Btu/h	12966	18766	27296	31390	40944	40944	42650	42650	54592	54592	58004	
SEER/SCOP		W/W	5.6/4.0	5.6/3.8	6.1/4.0	6.1/4.0	6.1/4	6.1/4	5.6/4	6.1/4.0	6.1/3.8	5.9/3.8	6.1/4	
Furnizimi me energji		Ph/V/Hz	220-240-50-1	220-240-50-1	220-240-50-1	220-240-50-1	220-240-50-1	220-240-50-1	220-240-50-1	380-415-50-3	220-240-50-1	380-415-50-3	380-415-50-3	
Fuqia ne hyrje	Ftohje	Kw	1.9	2.5	3.8	3.9	4.65	4.8	4.75	4.8	6.7	6.7	7.4	
	Ngrohje	Kw	1.8	2.4	4	4.1	4.85	4.85	4.9	4.9	6.5	6.7	7.2	
Rryma ne hyrje	Ftohje	A	5	7.2	10.1	12.4	15	5.4	18.1	6.7	21.3	8.9	9.8	
	Ngrohje	A	4.9	7.6	10.2	12	16.2	5.8	17.6	6.6	20.8	7.8	8.2	
Volumi i ngarkeses se gazit		Kg	1.2	1.4	2.2	2.4	3.5	3.5	3.7	3.7	4	4	5	
Njesia e brendshme	Niveli i presionit te zhurmes (H/M/L)		dB(A)	46/45/41/36	47/46/44/37	47/46/42/38	49/48/45/40	51/49/46/43	51/49/46/43	51/49/46/43	51/49/46/43	53/52/47/41	53/52/47/41	55/53/47/41
	Volumi i fryrjes se ajrit		CFM	412.00	447.00	765.00	883.0	1094.61	1094.61	1094.61	1094.61	1353.55	1353.55	1412.4
			m³/h	700	760	1300	1500	1860	1860	1860	1860	2300	2300	2400
	Dimensionet (GjxThxL)	E jashtme	mm	596x596x240	596x596x240	840x840x240	840x840x320	840x840x320	840x840x320	840x840x320	840x840x320	910x910x290	910x910x290	910x910x290
Pesha neto/ bruto	Paketimi	mm	773x733x300	773x733x300	963x963x325	963x963x409	963x963x409	963x963x409	963x963x409	963x963x409	1023x993x375	1023x993x375	1023x993x375	
		Kg	20/24	20/24	26/32	31/38	31/38	31/38	31/38	31/38	43/50	43/50	43/50	
Paneli	Dimensionet (LxGjxTh)	E jashtme	mm	670x670x50	670x670x50	950x950x60	950x950x60	950x950x60	950x950x60	950x950x60	950x950x60	1040x1040x65	1040x1040x65	1040x1040x65
	Pesha neto/ bruto	Paketimi	mm	763x763x105	763x763x105	1028x1043x130	1028x1043x130	1028x1043x130	1028x1043x130	1028x1043x130	1028x1043x130	1137x1137x140	1137x1137x140	1137x1137x140
		Kg	3.5/5	3.5/5	7/11	7/11	7/11	7/11	7/11	7/11	8/12	8/12	8/12	
Njesia e jashtme	Niveli i presionit te zhurmes		dB(A)	52	56	57	58	63	63	61	61	59	59	63
	Dimensionet (LxGjxTh)	E jashtme	mm	848x320x540	955x396x700	980x427x790	980x427x790	1107x440x1100	1107x440x1100	958x412x1349	958x412x1349	958x412x1349	958x412x1349	1085x427x1365
		Paketimi	mm	881x363x595	1029x458x750	1083x488x855	1083x488x855	1158x493x1236	1158x493x1236	1043x453x1500	1043x453x1500	1043x453x1500	1043x453x1500	1143x478x1505
	Pesha neto/ bruto	Kg	34/37	47/50	67/72	71/76	92/100	98/106	95/105	108/118	105/115	114/124	126/138	
Lidhja e tubit	Diametri i jashtem	Likuid	inch(mm)	1/4	1/4	3/8	3/8	3/8	3/8	3/8	3/8	3/8	3/8	
		Gaz	inch(mm)	3/8	1/2	5/8	5/8	5/8	5/8	5/8	5/8	5/8	3/4	
	Distanca maksimale	Lartesia	m	15	15	15	15	15	15	30	30	30	30	
		Gjatesia	m	20	20	30	30	30	30	50	50	50	50	



Casette Type R410 Dc Inverter

U-Match Inverter Kasete														
Model	Outdoor unit			GUHD12NK3FO	GUHD18NK3FO	GUHD24NK3FO	GUHD30NK3FO	GUHD36NK3FO	GUHD36NM3FO	GUHD42NK3FO	GUHD42NM3FO	GUHD48NK3FO	GUHD48NM3FO	GUHD60NM3FO
	Indoor unit			Cassette GKH12K3FI	Cassette GKH18K3FI	Cassette GKH24K3FI	Cassette GKH30K3FI	Cassette GKH36K3FI	Cassette GKH36K3FI	Cassette GKH42K3FI	Cassette GKH42K3FI	Cassette GKH48K3FI	Cassette GKH48K3FI	Cassette GKH60K3FI
Capacity	Cooling	W		3500	5000	7000	8300	1000	1000	11000	11000	14000	14000	16000
		Btu/h		11942	17060	23884	28319.6	34120	34120	37532	37532	47768	47768	54592
	Heating	W		3800	5600	8000	9200	12000	12000	12500	12500	16000	16000	17000
		Btu/h		12966	18766	27296	31390	40944	40944	42650	42650	54592	54592	58004
SEER/SCOP		W/W		5.6/4.0	5.6/3.8	6.1/4.0	6.1/4.0	6.1/4	6.1/4	5.6/4	6.1/4.0	6.1/3.8	5.9/3.8	6.1/4
Power supply		Ph/V/Hz		220-240-50-1	220-240-50-1	220-240-50-1	220-240-50-1	220-240-50-1	220-240-50-1	220-240-50-1	220-240-50-1	380-415-50-3	220-240-50-1	380-415-50-3
Power input	Cooling	Kw		1.9	2.5	3.8	3.9	4.65	4.8	4.75	4.8	6.7	6.7	7.4
	Heating	Kw		1.8	2.4	4	4.1	4.85	4.85	4.9	4.9	6.5	6.7	7.2
Current input	Cooling	A		5	7.2	10.1	12.4	15	5.4	18.1	6.7	21.3	8.9	9.8
	Heating	A		4.9	7.6	10.2	12	16.2	5.8	17.6	6.6	20.8	7.8	8.2
Refrigerant charge volume			Kg		1.2	1.4	2.2	2.4	3.5	3.5	3.7	4	4	5
Indoor unit	Sound pressure level (H/M/L)		dB(A)	46/45/41/36	47/46/44/37	47/46/42/38	49/48/45/40	51/49/46/43	51/49/46/43	51/49/46/43	51/49/46/43	53/52/47/41	53/52/47/41	55/53/47/41
	Airflow volume		CFM	412.00	447.00	765.00	883.0	1094.61	1094.61	1094.61	1094.61	1353.55	1353.55	1412.4
			m³/h		700	760	1300	1500	1860	1860	1860	2300	2300	2400
	Dimensions (WxDxH)	outline	mm	596x596x240	596x596x240	840x840x240	840x840x320	840x840x320	840x840x320	840x840x320	840x840x320	910x910x290	910x910x290	910x910x290
	Net weight/Gross weight	package	mm	773x733x300	773x733x300	963x963x325	963x963x409	963x963x409	963x963x409	963x963x409	963x963x409	1023x993x375	1023x993x375	1023x993x375
			Kg	20/24	20/24	26/32	31/38	31/38	31/38	31/38	31/38	43/50	43/50	43/50
Panel	Dimensions (WxDxH)	outline	mm	670x670x50	670x670x50	950x950x60	950x950x60	950x950x60	950x950x60	950x950x60	950x950x60	1040x1040x65	1040x1040x65	1040x1040x65
	package	mm	763x763x105	763x763x105	1028x1043x130	1028x1043x130	1028x1043x130	1028x1043x130	1028x1043x130	1028x1043x130	1028x1043x130	1137x1137x140	1137x1137x140	1137x1137x140
Net weight/Gross weight			Kg	3.5/5	3.5/5	7/11	7/11	7/11	7/11	7/11	7/11	8/12	8/12	8/12
Sound pressure level (H/M/L)			dB(A)	52	56	57	58	63	63	61	61	59	59	63
Outdoor unit	Dimensions (WxDxH)	outline	mm	848x320x540	955x396x700	980x427x790	980x427x790	1107x440x1100	1107x440x1100	958x412x1349	958x412x1349	958x412x1349	958x412x1349	1085x427x1365
	package	mm	881x363x595	1029x458x750	1083x488x855	1083x488x855	1158x493x1236	1158x493x1236	1158x493x1236	1043x453x1500	1043x453x1500	1043x453x1500	1043x453x1500	1143x478x1505
Net weight/Gross weight			Kg	34/37	47/50	67/72	71/76	92/100	98/106	95/105	108/118	105/115	114/124	126/138
Connecting pipe	Outer diameter	liquid	inch(mm)	1/4	1/4	3/8	3/8	3/8	3/8	3/8	3/8	3/8	3/8	3/8
		Gas	inch(mm)	3/8	1/2	5/8	5/8	5/8	5/8	5/8	5/8	5/8	5/8	3/4
	Max. distances	Height	m	15	15	15	15	15	15	15	30	30	30	30
		Length	m	20	20	30	30	30	30	30	50	50	50	50