



Cassette Type R410 On-Off

U-Match On/Off Kasete										
Modeli	Njesia e jashtme		GUHN18NK3AO	GUHN24NK3AO	GUHN30NK3A1O	GUHN36NM3AO	GUHN42NM3AO	GUHN48NM3AO	GUHN60NM3AO	
	Njesia e brendshme		GKH18K3BI	GKH24K3BI	GKH30K3BI	GKH36K3BI	GKH42K3BI	GKH48K3BI	GKH60K3BI	
Kapaciteti	Ftohje	W	5000	6800	8300	10000	12000	13200	15500	
		Btu/h	17060	23200	28320	34120	40940	45040	52800	
	Ngrohje	W	5400	7500	8800	11000	14000	14500	18500	
		Btu/h	18430	25600	30020	37530	47770	49470	63120	
EER/COP	W/W		2.5/2.84	2.6/3	2.86/2.79	2.78/3.55	2.5/2.8	2.75/2.79	2.58/3.49	
Furnizimi me energji	Ph/V/Hz		1,220-240,50	1,220-240,50	1,220-240,50	3,380-415,50	3,380-415,50	3,380-415,5	3,380-415,50	
Fuqia ne hyrje	Ftohje	Kw	2	2.62	2.9	3.6	4.8	4.8	6	
	Ngrohje	Kw	1.9	2.5	3.15	3.3	5	5.2	5.3	
Rryma ne hyrje	Ftohje	A	9	11.9	13.1	6.7	8.7	8.7	10.9	
	Ngrohje	A	8.7	11.4	13.1	5.7	8.5	9.5	9.6	
Volumi i ngarkeses se gazit	Kg		1.5	2.2	3.0	3.2	3.55	3.8	4.5	
Njesia e brendshme	Volumi I fryrjes se ajrit		m³/h	550/490/420	1180/1080/1000	1400/1270/1170	1660/1570/1500	1660/1570/1500	1660/1570/1500	2300/2100/1900
	Niveli i presionit te zhurmes (H/M/L)		dB(A)	47/45/43	47/45/43	51/49/48	53/51/48	53/51/48	53/51/48	58/55/52
	Dimensionet (GjxThxL)	E jashtme	mm	600x600x230	840x840x240	840x840x240	840x840x320	840x840x320	840x840x320	1700x700x245
		Paketimi	mm	851x681x325	963x363x325	963x963x325	963x963x409	963x963x409	963x963x409	1825x825x330
	Pesha neto/ bruto		Kg	20/27	27/36	27/36	32/43	32/43	32/43	65/73
Paneli	Dimensionet (GjxThxL)	E jashtme	mm	650x650x50	950x950x60	950x950x60	950x950x60	950x950x60	950x950x60	
		Paketimi	mm	670x730x102	1025x1040x115	1025x1040x115	1025x1040x115	1025x1040x115	1028x1043x130	
	Pesha neto/ bruto		Kg	2.5/3.5	6.5/10	6.5/10	6.5/10	6.5/10	7/11	
Njesia e jashtme	Niveli i presionit te zhurmes		dB(A)	56	59	59	60	60	63	64
	Dimensionet (GjxThxL)	E jashtme	mm	820x320x540	1018x412x695	980x427x790	1018x412x840	1032x412x1250	1032x412x1250	1032x412x1250
		Paketimi	mm	873x363x605	1103x453x770	1083x488x855	1103x453x1000	1113x453x1400	1113x453x1400	1113x453x1400
	Pesha neto/ bruto		Kg	40/45	59/64	70/75	90/100	112/123	112/123	123/134
Lidhja e tubit	Diametri i jashtem	Likuid	inch(mm)	1/4	3/8	3/8	1-Feb	1/2	1/2	1/2
		Gaz	inch(mm)	1/2	5/8	5/8	3/4	3/4	3/4	3/4
	Max. distances		L/Gj	m	15/20	15/30	15/30	30/50	30/50	30/50



Cassette Type R410 On-Off

U-Match On/Off Kasete										
Model	Outdoor unit		GUHN18NK3AO	GUHN24NK3AO	GUHN30NK3A1O	GUHN36NM3AO	GUHN42NM3AO	GUHN48NM3AO	GUHN60NM3AO	
	Indoor unit		GKH18K3BI	GKH24K3BI	GKH30K3BI	GKH36K3BI	GKH42K3BI	GKH48K3BI	GKH60K3BI	
Capacity	Cooling	W	5000	6800	8300	10000	12000	13200	15500	
		Btu/h	17060	23200	28320	34120	40940	45040	52800	
	Heating	W	5400	7500	8800	11000	14000	14500	18500	
		Btu/h	18430	25600	30020	37530	47770	49470	63120	
EER/COP		W/W	2.5/2.84	2.6/3	2.86/2.79	2.78/3.55	2.5/2.8	2.75/2.79	2.58/3.49	
Power supply		Ph/V/Hz	1,220-240,50	1,220-240,50	1,220-240,50	3,380-415,50	3,380-415,50	3,380-415,5	3,380-415,50	
Power input	Cooling	Kw	2	2.62	2.9	3.6	4.8	4.8	6	
	Heating	Kw	1.9	2.5	3.15	3.3	5	5.2	5.3	
Current input	Cooling	A	9	11.9	13.1	6.7	8.7	8.7	10.9	
	Heating	A	8.7	11.4	13.1	5.7	8.5	9.5	9.6	
Refrigerant charge volume		Kg	1.5	2.2	3.0	3.2	3.55	3.8	4.5	
Indoor unit	Airflow Volume		m ³ /h	550/490/420	1180/1080/1000	1400/1270/1170	1660/1570/1500	1660/1570/1500	1660/1570/1500	2300/2100/1900
	Sound pressure level		dB(A)	47/45/43	47/45/43	51/49/48	53/51/48	53/51/48	53/51/48	58/55/52
	Dimensions (WxDxH)	outline	mm	600x600x230	840x840x240	840x840x240	840x840x320	840x840x320	840x840x320	1700x700x245
		package	mm	851x681x325	963x363x325	963x963x325	963x963x409	963x963x409	963x963x409	1825x825x330
	Net weight/Gross weight		Kg	20/27	27/36	27/36	32/43	32/43	32/43	65/73
Panel	Dimensions (WxDxH)	outline	mm	650x650x50	950x950x60	950x950x60	950x950x60	950x950x60	950x950x60	
		package	mm	670x730x102	1025x1040x115	1025x1040x115	1025x1040x115	1025x1040x115	1028x1043x130	
	Net weight/Gross weight		Kg	2.5/3.5	6.5/10	6.5/10	6.5/10	6.5/10	7/11	
Outdoor unit			dB(A)	56	59	59	60	60	63	64
	Dimensions (WxDxH)	outline	mm	820x320x540	1018x412x695	980x427x790	1018x412x840	1032x412x1250	1032x412x1250	1032x412x1250
		package	mm	873x363x605	1103x453x770	1083x488x855	1103x453x1000	1113x453x1400	1113x453x1400	1113x453x1400
	Net weight/Gross weight		Kg	40/45	59/64	70/75	90/100	112/123	112/123	123/134
Connecting pipe	Outer diameter	liquid	inch(mm)	1/4	3/8	3/8	1-Feb	1/2	1/2	1/2
		gas	inch(mm)	1/2	5/8	5/8	3/4	3/4	3/4	3/4
	Max. distances	height/length	m	15/20	15/30	15/30	30/50	30/50	30/50	30/50