



### Cassette Type R410 On-Off

U-Match On/Off Kasete										
Modeli	Njesia e jashtme		GUHN18NK3AO	GUHN24NK3AO	GUHN30NK3A1O	GUHN36NM3AO	GUHN42NM3AO	GUHN48NM3AO	GUHN60NM3AO	
	Njesia e brendshme		GKH18K3BI	GKH24K3BI	GKH30K3BI	GKH36K3BI	GKH42K3BI	GKH48K3BI	GKH60K3BI	
Kapaciteti	Ftohje	W	5000	6800	8300	10000	12000	13200	15500	
		Btu/h	17060	23200	28320	34120	40940	45040	52800	
	Ngrohje	W	5400	7500	8800	11000	14000	14500	18500	
		Btu/h	18430	25600	30020	37530	47770	49470	63120	
EER/COP	W/W		2.5/2.84	2.6/3	2.86/2.79	2.78/3.55	2.5/2.8	2.75/2.79	2.58/3.49	
Furnizimi me energji	Ph/V/Hz		1,220-240,50	1,220-240,50	1,220-240,50	3,380-415,50	3,380-415,50	3,380-415,5	3,380-415,50	
Fuqia ne hyrje	Ftohje	Kw	2	2.62	2.9	3.6	4.8	4.8	6	
	Ngrohje	Kw	1.9	2.5	3.15	3.3	5	5.2	5.3	
Rryma ne hyrje	Ftohje	A	9	11.9	13.1	6.7	8.7	8.7	10.9	
	Ngrohje	A	8.7	11.4	13.1	5.7	8.5	9.5	9.6	
Volumi i ngarkeses se gazit	Kg		1.5	2.2	3.0	3.2	3.55	3.8	4.5	
Njesia e brendshme	Volumi I fryrjes se ajrit		m³/h	550/490/420	1180/1080/1000	1400/1270/1170	1660/1570/1500	1660/1570/1500	1660/1570/1500	2300/2100/1900
	Niveli i presionit te zhurmes (H/M/L)		dB(A)	47/45/43	47/45/43	51/49/48	53/51/48	53/51/48	53/51/48	58/55/52
	Dimensionet (GjxThxL)	E jashtme	mm	600x600x230	840x840x240	840x840x240	840x840x320	840x840x320	840x840x320	1700x700x245
		Paketimi	mm	851x681x325	963x363x325	963x963x325	963x963x409	963x963x409	963x963x409	1825x825x330
	Pesha neto/ bruto		Kg	20/27	27/36	27/36	32/43	32/43	32/43	65/73
Paneli	Dimensionet (GjxThxL)	E jashtme	mm	650x650x50	950x950x60	950x950x60	950x950x60	950x950x60	950x950x60	
		Paketimi	mm	670x730x102	1025x1040x115	1025x1040x115	1025x1040x115	1025x1040x115	1028x1043x130	
	Pesha neto/ bruto		Kg	2.5/3.5	6.5/10	6.5/10	6.5/10	6.5/10	7/11	
Njesia e jashtme	Niveli i presionit te zhurmes		dB(A)	56	59	59	60	60	63	64
	Dimensionet (GjxThxL)	E jashtme	mm	820x320x540	1018x412x695	980x427x790	1018x412x840	1032x412x1250	1032x412x1250	1032x412x1250
		Paketimi	mm	873x363x605	1103x453x770	1083x488x855	1103x453x1000	1113x453x1400	1113x453x1400	1113x453x1400
	Pesha neto/ bruto		Kg	40/45	59/64	70/75	90/100	112/123	112/123	123/134
Lidhja e tubit	Diametri i jashtem	Likuid	inch(mm)	1/4	3/8	3/8	1-Feb	1/2	1/2	1/2
		Gaz	inch(mm)	1/2	5/8	5/8	3/4	3/4	3/4	3/4
	Max. distances		L/Gj	m	15/20	15/30	15/30	30/50	30/50	30/50



### Cassette Type R410 On-Off

U-Match On/Off Kasete										
Model	Outdoor unit		GUHN18NK3AO	GUHN24NK3AO	GUHN30NK3A1O	GUHN36NM3AO	GUHN42NM3AO	GUHN48NM3AO	GUHN60NM3AO	
	Indoor unit		GKH18K3BI	GKH24K3BI	GKH30K3BI	GKH36K3BI	GKH42K3BI	GKH48K3BI	GKH60K3BI	
Capacity	Cooling	W	5000	6800	8300	10000	12000	13200	15500	
		Btu/h	17060	23200	28320	34120	40940	45040	52800	
	Heating	W	5400	7500	8800	11000	14000	14500	18500	
		Btu/h	18430	25600	30020	37530	47770	49470	63120	
EER/COP		W/W	2.5/2.84	2.6/3	2.86/2.79	2.78/3.55	2.5/2.8	2.75/2.79	2.58/3.49	
Power supply		Ph/V/Hz	1,220-240,50	1,220-240,50	1,220-240,50	3,380-415,50	3,380-415,50	3,380-415,5	3,380-415,50	
Power input	Cooling	Kw	2	2.62	2.9	3.6	4.8	4.8	6	
	Heating	Kw	1.9	2.5	3.15	3.3	5	5.2	5.3	
Current input	Cooling	A	9	11.9	13.1	6.7	8.7	8.7	10.9	
	Heating	A	8.7	11.4	13.1	5.7	8.5	9.5	9.6	
Refrigerant charge volume		Kg	1.5	2.2	3.0	3.2	3.55	3.8	4.5	
Indoor unit	Airflow Volume		m <sup>3</sup> /h	550/490/420	1180/1080/1000	1400/1270/1170	1660/1570/1500	1660/1570/1500	1660/1570/1500	2300/2100/1900
	Sound pressure level		dB(A)	47/45/43	47/45/43	51/49/48	53/51/48	53/51/48	53/51/48	58/55/52
	Dimensions ( WxDxH)	outline	mm	600x600x230	840x840x240	840x840x240	840x840x320	840x840x320	840x840x320	1700x700x245
		package	mm	851x681x325	963x363x325	963x963x325	963x963x409	963x963x409	963x963x409	1825x825x330
	Net weight/Gross weight		Kg	20/27	27/36	27/36	32/43	32/43	32/43	65/73
Panel	Dimensions ( WxDxH)	outline	mm	650x650x50	950x950x60	950x950x60	950x950x60	950x950x60	950x950x60	
		package	mm	670x730x102	1025x1040x115	1025x1040x115	1025x1040x115	1025x1040x115	1028x1043x130	
	Net weight/Gross weight		Kg	2.5/3.5	6.5/10	6.5/10	6.5/10	6.5/10	7/11	
Outdoor unit			dB(A)	56	59	59	60	60	63	64
	Dimensions ( WxDxH)	outline	mm	820x320x540	1018x412x695	980x427x790	1018x412x840	1032x412x1250	1032x412x1250	1032x412x1250
		package	mm	873x363x605	1103x453x770	1083x488x855	1103x453x1000	1113x453x1400	1113x453x1400	1113x453x1400
	Net weight/Gross weight		Kg	40/45	59/64	70/75	90/100	112/123	112/123	123/134
Connecting pipe	Outer diameter	liquid	inch(mm)	1/4	3/8	3/8	1-Feb	1/2	1/2	1/2
		gas	inch(mm)	1/2	5/8	5/8	3/4	3/4	3/4	3/4
	Max. distances	height/length	m	15/20	15/30	15/30	30/50	30/50	30/50	30/50