



Console GMV5

Modeli			GMV-ND22C/A-T	GMV-ND28C/A-T	GMV-ND36C/A-T	GMV-ND45C/A-T	GMV-ND50C/A-T
Kapaciteti	Ftohje	Kw	2.2	2.8	3.6	5.4	5.0
	Ngrohje	Kw	2.5	3.2	4.0	5.0	5.5
Furnizimi me energji		V/Ph/Hz	220~240/1/50 & 208~230/1/60				
Konsumi i energjise		W	15	15	20	40	40
Volumi i fryrjes se ajrit		m ³ /h	430-400/320/270	430-400/320/270	570-480/400/300	280-680/600/500	280-680/600/500
		CFM	253-235/188/159	253-235/188/159	335-282/235/188	460-400/353/294	460-400/353/294
Rryma nominale	Ftohje	A	0.15	0.15	0.15	0.15	0.15
	Ngrohje	A	0.15	0.15	0.15	0.15	0.15
	Ngrohje uji	A	/	/	/	/	/
Niveli i presionit te zhurmes		dB(A)	38/33/27	38/33/27	40/37/32	46/43/39	46/43/39
Lidhja e tubit	Likuid	mm	ø6.35	ø6.35	ø6.35	ø6.35	ø6.35
	Gaz	mm	ø9.52	ø9.52	ø9.52	ø9.52	ø9.52
Tubi i shkarkimit	Dia. jashtem	mm	ø17.2	ø17.2	ø17.2	ø17.2	ø17.2
	Trashesia	mm	1	1	1	1	1
Dimensionet (GJxThxL)	E jashtme	mm	700x215x600	700x215x600	700x215x600	700x215x600	700x215x600
	Paketimi	mm	788x283x697	788x283x697	788x283x697	788x283x697	788x283x697
Pesha neto/ bruto		kg	16/19	16/19	16/19	16/19	16/19
Ngarkesa	40'GP	set	387	387	387	387	387
	40'HQ	set	433	433	433	433	433