



Njesite Outdoor Inverter

Outdoor Free Match 4&4+									
Modeli			GWHD(14)NK3DO	GWHD(18)NK3KCG	GWHD(21)NK3KCG	GWHD(24)NK3MO	GWHD(28)NK3KO	GWHD(36)NK3BO	GWHD(42)NK3AO
Kapaciteti	Ftohje	Btu/h	14000	18000	21000	24000	28000	35826	41285
	Ngrohje	Btu/h	15000	18400	22000	29000	31800	37532	44400
SEER		W/W	6.1	6.3	6.1	6.1	6.1	5.5	5.5
Furnizimi me energji		Ph/V/Hz	1Ph,220-240V, 50Hz						
Fuqia ne hyrje	Ftohje	Kw	1.2	1.45	1.91	2.18	2.54	3.5	3.59
	Ngrohje	Kw	1.18	1.45	1.73	2.28	2.49	3.75	3.54
Volumi i ngarkeses se gazit		Kg	1.4	1.4	2.2	2.2	2.4	4.3	4.8
Volumi i fryrjes se ajrit		m ³ /h	2600	3200	3200	4000	4000	5200	5500
Niveli i presionit te zhurmes		dB(A)	55	56	56	58	58	57	54
Dimensionet (LxGjxTh)	E jashtme	mm	899x596x378	955x396x700	955x396x700	980x427x790	980x427x790	1015x440x1103	1015x440x1103
	Paketimi	mm	948x645x420	1029x750x458	1029x750x458	1083x488x855	1083x488x855	1158x493x1235	1158x493x1235
Pesha neto/ bruto		Kg	43/46	51/55.5	62/66.5	68/73	69/74	94/104	102/112
Lidhja e tubit	gaz	nch(mm)	3/8	3/8	3/8	3/8	3/8	3/8	1/2
	likuid	nch(mm)	1/4	1/4	1/4	1/4	1/4	1/4	1/4
Max. gjatesise se tubit		m	20	20	60	60	70	70	80
Nr. Max i Indooreve qe		njesi	5	5	5	5	5	5	5

Funksioni	Kushtet nominale operative (temperatura)				Gama e operimit (temperatura)	
	Kushtet e indoor		Kushtet e outdoor		Kushtet outdoor (Free Match 4)	Kushtet outdoor (Free Match 4+)
	DB(°C)	WB(°C)	DB(°C)	WB(°C)	DB(°C)	DB(°C)
Ftohje	35	24	27	19	-15~43	18~43
Ngrohje	7	6	20	15	-20~24	-15~24