



### Duct Type R410 On-Off

U-Match On/Off Kanalor										
Modeli	Njesia e jashtme		GUHN18NK3AO	GUHN24NK3AO	GUHN30NK3A1O	GUHN36NM3AO	GUHN42NM3AO	GUHN48NM3A1O	GUHN60NMA2O	
	Njesia e brendshme		GFH18K3BI	GFH24K3BI	GFH30K3B1I	GFH30K3BI	GFH42K3BI	GFH48K3B1I	GFH60K3B2I	
Kapaciteti	Ftohje	W	5000	7000	8300	9800	12000	13200	15500	
		Btu/h	17060	23880	28320	33440	40940	45050	52800	
	Ngrohje	W	5700	8000	9100	11000	14000	14500	18500	
		Btu/h	19450	27300	31050	37530	47770	49470	63120	
EER/COP	W/W		2.38/3.17	2.63/3.19	2.77/3.03	2.45/3.14	2.26/2.86	2.59/3.15	2.5/3.49	
Furnizimi me energji	Ph/V/Hz		1,220-240,50	1,220-240,50	1,220-240,50	3,380-415,5	3,380-415,50	3,380-415,5	3,380-415,5	
Fuqia ne hyrje	Ftohje	Kw	2.1	2.66	3	4	5.3	5.1	6.2	
	Ngrohje	Kw	1.8	2.51	3	3.5	4.9	4.6	5.3	
Rryma ne hyrje	Ftohje	A	9.4	12.1	13.5	7	9.6	9.2	11.3	
	Ngrohje	A	8	11.4	13.9	6.3	8.9	8.3	9.6	
Volumi i ngarkeses se gazit	Kg		1.5	2.2	3.0	3.2	3.55	3.8	5	
Njesia e brendshme	Volumi i fryrjes se ajrit		m <sup>3</sup> /h	840/750/680	1600/1400/1200	1500/1300/1100	2000/1900/1800	2000/1900/1800	2300/2110/1850	2500/2070/1730
	ESP	Kategoria	Pa	25	25	37	37	37	50	50
		Gama	Pa	0-25	0-100	0-100	0-150	0-150	0-150	0-50
	Niveli i presionit te zhurmes (H/M/L)		dB(A)	42/40/38	47/44/42	47/44/42	50/48/46	50/48/46	53/50/46	53/50/48
	Dimensionet (GjxThxL)	E jashtme	mm	1012x736x266	1270x530x268	1270x530x268	1226x775x290	1226x775x290	1226x775x290	1226x815x330
		Paketimi	mm	1123x798x323	1348x597x283	1348x597x283	1338x837x305	1338x837x305	1338x837x305	1338x885x345
	Pesha neto/ bruto		Kg	34/41	37/43	37/43	54/61	54/61	57/67	66/76
Njesia e jashtme	Niveli i presionit te zhurmes		dB(A)	56	59	59	60	60	63	64
	Dimensionet (GjxThxL)	E jashtme	mm	820x320x540	1018x412x695	980x427x790	1018x412x840	1032x412x1250	1032x412x1250	1032x412x1250
		Paketimi	mm	873x363x605	1103x453x770	1083x488x855	1103x453x1000	1113x453x1400	1113x453x1400	1113x453x1400
	Pesha neto/ bruto		Kg	40/45	59/64	70/75	90/100	112/123	112/123	123/134
Lidhja e tubit	Diametri i jashtem	Likuid	inch(mm)	1/4	3/8	3/8	1/2	1/2	1/2	
		Gaz	inch(mm)	1/2	5/8	5/8	3/4	3/4	3/4	
	Max. distances		L/Gj	m	15/20	15/30	15/30	30/50	30/50	30/50



### Duct Type R410 On-Off

U-Match On/Off Duct											
Model	Outdoor Unit		GUHN18NK3AO	GUHN24NK3AO	GUHN30NK3A1O	GUHN36NM3AO	GUHN42NM3AO	GUHN48NM3A1O	GUHN60NMA2O		
	Indoor Unit		GFH18K3BI	GFH24K3BI	GFH30K3B1I	GFH30K3BI	GFH42K3BI	GFH48K3B1I	GFH60K3B2I		
Capacity	Cooling	W	5000	7000	8300	9800	12000	13200	15500		
		Btu/h	17060	23880	28320	33440	40940	45050	52800		
	Heating	W	5700	8000	9100	11000	14000	14500	18500		
		Btu/h	19450	27300	31050	37530	47770	49470	63120		
EER/COP		W/W	2.38/3.17	2.63/3.19	2.77/3.03	2.45/3.14	2.26/2.86	2.59/3.15	2.5/3.49		
Power supply		Ph/V/Hz	1,220-240,50	1,220-240,50	1,220-240,50	3,380-415,5	3,380-415,50	3,380-415,5	3,380-415,5		
Power input	Cooling	Kw	2.1	2.66	3	4	5.3	5.1	6.2		
	Heating	Kw	1.8	2.51	3	3.5	4.9	4.6	5.3		
Current input	Cooling	A	9.4	12.1	13.5	7	9.6	9.2	11.3		
	Heating	A	8	11.4	13.9	6.3	8.9	8.3	9.6		
Refrigerant charge input		Kg	1.5	2.2	3.0	3.2	3.55	3.8	5		
Indoor Unit	Airflow volume		m <sup>3</sup> /h	840/750/680	1600/1400/1200	1500/1300/1100	2000/1900/1800	2000/1900/1800	2300/2110/1850	2500/2070/1730	
	ESP	Rated	Pa	25	25	37	37	37	50	50	
		Range	Pa	0-25	0-100	0-100	0-150	0-150	0-150	0-50	
	Sound pressure level			dB(A)	42/40/38	47/44/42	47/44/42	50/48/46	50/48/46	53/50/46	53/50/48
	Dimensions ( WxDxH)	Outline	mm	1012x736x266	1270x530x268	1270x530x268	1226x775x290	1226x775x290	1226x775x290	1226x815x330	
		Package	mm	1123x798x323	1348x597x283	1348x597x283	1338x837x305	1338x837x305	1338x837x305	1338x885x345	
Net weight/ Gross weight			Kg	34/41	37/43	37/43	54/61	54/61	57/67	66/76	
Outdoor Unit	Sound pressure level			dB(A)	56	59	59	60	60	63	64
	Dimensions ( WxDxH)	Outline	mm	820x320x540	1018x412x695	980x427x790	1018x412x840	1032x412x1250	1032x412x1250	1032x412x1250	
		Package	mm	873x363x605	1103x453x770	1083x488x855	1103x453x1000	1113x453x1400	1113x453x1400	1113x453x1400	
	Net weight/ Gross weight			Kg	40/45	59/64	70/75	90/100	112/123	112/123	123/134
Connecting pipe	outer diameter	Liquid	inch(mm)	1/4	3/8	3/8	1/2	1/2	1/2	1/2	
		Gas	inch(mm)	1/2	5/8	5/8	3/4	3/4	3/4	3/4	
	Max. distances			H/L	m	15/20	15/30	15/30	30/50	30/50	30/50