



Floor Standing Dc Inverter

Model			GVH24AK-K3DNC6A
Funksioni			Ngrohes/Ftohes
Kapaciteti	Ftohe	Btu/h	24700(4700~27600)
	Ngrohje	Btu/h	27600(4800~34000)
EER/C.O.P		W/W	3.1/3.09
Power Supply		Ph,V,Hz	1Ph,220-240V,50Hz
Fuqia ne hyrje	Ftohe	W	2340(315~3200)
	Ngrohje	W	2860(340~3600)
Intensiteti I rrymes	Ftohe	A	25.9
	Ngrohje	A	25.9
Volumi I fryrjes se ajrit		m3/h	1200/930/840/752
Njesia e brendshme			
Niveli I presionit te zhurmes		dB(A)(SH/h/M/L)	47/43/40/38
Dimensionet e produktit	I jashtem	mm	480x1687x394
	paketimi	mm	538x1828x530
Pesha		kg	49/67
Njesia e jashtme			
Niveli I presionit te zhurmes		dB(A)	56
Lidhja e tubave	Gaz	mm	ø16
	leng	mm	ø6
Dimensionet e produktit	I jashtem	mm	955x700x396
	paketimi	mm	1029x750x458
Pesha		kg	56/63



Floor Standing Dc Inverter

Model			GVH24AK-K3DNC6A
Function			Cooling/Heating
Capacity	Cooling	Btu/h	24700(4700~27600)
	Heating	Btu/h	27600(4800~34000)
EER/C.O.P		W/W	3.1/3.09
Power Supply		Ph,V,Hz	1Ph,220-240V,50Hz
Power input	Cooling	W	2340(315~3200)
	Heating	W	2860(340~3600)
Rated current	Cooling	A	25.9
	Heating	A	25.9
Airflow		m3/h	1200/930/840/752
Indoor unit			
Sound preesure level		dB(A)(SH/h/M/L)	47/43/40/38
Dimensions (WxDxH)	outline	mm	480x1687x394
	package	mm	538x1828x530
Net weight/Gross weight		kg	49/67
Outdoor unit			
Sound preesure level		dB(A)	56
Connecting pipe	Gas	mm	ø16
	Liquid	mm	ø6
Dimensions (WxDxH)	outline	mm	955x700x396
	package	mm	1029x750x458
Net weight/Gross weight		kg	56/63