



### Floor Standing GMV5

Modeli			GMV-ND100L/A-T	GMV-ND140L/A-T
Kapaciteti	Ftohje	Kw	10	14
	Ngrohje	Kw	11	15
Furnizimi me energji		V/Ph/Hz	220~240/1/50 & 208~230/1/60	
Konsumi i energjise		W	185	185
Volumi i fryrjes se ajrit		m <sup>3</sup> /h	1850/1600/1400	1850/1600/1400
		CFM	1089/942/824	1089/942/824
Rryma nominale	Ftohje	A	1.5	1.5
	Ngrohje	A	1.5	1.5
	Ngrohje uji	A	/	/
ESP		Pa	0	0
Niveli i presionit te zhurmes		dB(A)	50/48/46	50/48/46
Lidhja e tubit	Likuid	mm	ø9	ø9
	Gaz	mm	ø16	ø16
Tubi i shkarkimit	Dia. jashtem	mm	ø31	ø31
	Trashesia	mm	4.5	4.5
Dimensionet (GJxThxL)	E jashtme	mm	1870x580x400	
	Paketimi	mm	2083x738x545	
Pesha neto/ bruto		kg	54/74	57/78
Ngarkesa	40'GP	set	67	67
	40'HQ	set	67	67