



### Floor Standing R410 On Off

Model			GVA48AH-M3NNA5B	GVA60AH-M3NNA5A
<b>Funksioni</b>			Ngrohes/Ftohes	Ngrohes/Ftohes
<b>Kapaciteti</b>	Ftohje	Btu/h	47,800	54,300
	Ngrohje	Btu/h	51,100	66,500
<b>EER/C.O.P</b>		W/W	2,51/2,83	2,57/2,98
<b>Furnizimi me energji</b>		Ph,V,Hz	1Ph,220-240V,50Hz	1Ph,220-240V,50Hz
<b>Fuqia ne hyrje</b>	Ftohje	kW	5,58	6,19
	Ngrohje	kW	5,30(8.80)	6,53(9,03)
<b>Intensiteti I rrymes</b>	Ftohje	A	8,5	9,7
	Ngrohje	A	8,0(13.3)	9,4(14,7)
<b>Volumi I fryrjes se ajrit</b>		m3/h	1,800	2,000
<b>Njesia e brendshme</b>				
<b>Niveli I presionit te zhurmes</b>		dB(A)(SH/h/M/L)	52/50/48/46	54/52/50/47
<b>Dimensionet e produktit</b>	LxHxD	mm	581x395x1870	581x395x1870
<b>Pesha</b>		kg	63/89	
<b>Njesia e jashtme</b>				
<b>Niveli I presionit te zhurmes</b>		dB(A)	59	63
<b>Lidhja e tubave</b>	Gaz	mm	1	1
	Likuid	mm	0.8	0.8
<b>Dimensionet e produktit</b>	LxHxD	mm	1032x412x1250	1032x412x1250
<b>Pesha</b>		kg	60/105	62/117



### Floor Standing R410 On Off

Model			GVA48AH-M3NNA5B	GVA60AH-M3NNA5A
Function			Cooling/Heating	Cooling/Heating
Capacity	Cooling	Btu/h	47,800	54,300
	Heating	Btu/h	51,100	66,500
EER/C.O.P		W/W	2,51/2,83	2,57/2,98
Power supply		Ph,V,Hz	1Ph,220-240V,50Hz	1Ph,220-240V,50Hz
Power input	Cooling	kW	5,58	6,19
	Heating	kW	5,30(8.80)	6,53(9,03)
Rated current	Cooling	A	8,5	9,7
	Heating	A	8,0(13.3)	9,4(14,7)
Airflow volume		m3/h	1,800	2,000
Indoor unit				
Sound pressure level		dB(A)(SH/h/M/L)	52/50/48/46	54/52/50/47
Dimensions	WxDxH	mm	581x395x1870	581x395x1870
Net weight/Gross weight		kg	63/89	
Outdoor unit				
Sound pressure level		dB(A)	59	63
Connecting pipe	Gas	mm	1	1
	Likuid	mm	0.8	0.8
Dimensions	WxDxH	mm	1032x412x1250	1032x412x1250
Net weight/Gross weight		kg	60/105	62/117