



Free Match Floor Ceiling Indoor Units Ecodesign

Modeli			GTH(09)AA-K3DNA1B/I	GTH(12)AA-K3DNA1B/I	GTH(18)AA-K3DNA1B/I	GTH(24)AA-K3DNA1B/I
Kapaciteti	Ftohje	Btu/h	8530	11942	17060	24225
	Ngrohje	Btu/h	9554	13136	18766	27296
Furnizimi me energji		Ph/V/Hz	1Ph,220-240V,50Hz			
Volumi i fryrjes se ajrit		m ³ /h	650	650	950	1250
		CFM	383	383	559	736
Niveli i presionit te zhurmes		dB(A)	40/36	40/36	45/40	48/44
Lidhja e tubave	Gas	inch(mm)	3/8(Ø9.52)	3/8(Ø9.52)	1/2(Ø12.7)	5/8(Ø15.88)
	Leng	inch(mm)	1/4(Ø6.35)	1/4(Ø6.35)	1/4(Ø6.35)	3/8(Ø9.52)
Dimensionet (LxGjxTh)	E jashtme	mm	1220X700X225	1220X700X225	1220X700X225	1220X700X225
	Paketimi	mm	1343X823X315	1343X823X315	1343X823X315	1343X823X315
Pesha		Kg	40/50	40/50	40/50	45/54