



Fresh Air Processing Duct

Model			GMV-NX140P/A(X1.2)-K*	GMV-NX224P/A(X2.0)-M*	GMV-NX280P/A(X2.5)-M*	GMV-NX280P/A(X3.0)-M*	GMV-NX450P/A(X4.0)-M*
Capacity	Cooling	Kw	14.0	22.4	28.0	28.0	45.0
	Heating	Kw	10.0	16.0	20.0	20.0	32.0
Power supply		V/Ph/Hz	220~240/1/50		380~2415/3/50		
Power consumption		W	360	740	760	1060	1240
Airflow volume		m ³ /h	1200	2000	2500	3000	4000
		CFM	705	1175	1470	1765	2355
Rated current	Cooling	A	1.82	1.32	1.36	1.89	2.22
	Heating	A	1.82	1.32	1.36	1.89	2.22
	Water heating	A	/	/	/	/	/
ESP		Pa	150	200			
Sound pressure level		dB(A)	42	47	48	51	52
Connecting pipe	Liquid	mm	ø9.52	ø9.52	ø9.52	ø9.52	ø12.7
	Gas	mm	ø15.9	ø19.05	ø22.2	ø22.2	ø28.6
Drain pipe	External dia.	mm	ø25	ø25	ø25	ø25	ø25
	Thickness	mm	2.5	2.5	2.5	2.5	2.5
Dimensions (WxDxH)	outline	mm	1463x756x300	1500x1000x500			1700x1100x650
	package	mm	1514x785x360	1840x1200x673			1890x1460x835
Net weight/Gross weight		kg	63.5/71	130/182	134/188	134/188	208/266
Loading quantity	40'GP	set	84.0	18.0	18.0	18.0	16.0
	40'HQ	set	98.0	18.0	18.0	18.0	16.0