



### Fresh Air Processing Duct

Modeli			GMV-NX140P/A(X1.2)-K*	GMV-NX224P/A(X2.0)-M*	GMV-NX280P/A(X2.5)-M*	GMV-NX280P/A(X3.0)-M*	GMV-NX450P/A(X4.0)-M*
Kapaciteti	Ftohje	Kw	14.0	22.4	28.0	28.0	45.0
	Ngrohje	Kw	10.0	16.0	20.0	20.0	32.0
Furnizimi me energji		V/Ph/Hz	220~240/1/50	380~2415/3/50			
Konsumi i energjise		W	360	740	760	1060	1240
Volumi i fryrjes se ajrit		m <sup>3</sup> /h	1200	2000	2500	3000	4000
		CFM	705	1175	1470	1765	2355
Rryma nominale	Ftohje	A	1.82	1.32	1.36	1.89	2.22
	Ngrohje	A	1.82	1.32	1.36	1.89	2.22
	Ngrohje uji	A	/	/	/	/	/
ESP		Pa	150	200			
Niveli i presionit te zhurmes		dB(A)	42	47	48	51	52
Lidhja e tubit	Likuid	mm	ø9.52	ø9.52	ø9.52	ø9.52	ø12.7
	Gaz	mm	ø15.9	ø19.05	ø22.2	ø22.2	ø28.6
Tubi i shkarkimit	Dia. jashtem	mm	ø25	ø25	ø25	ø25	ø25
	Trashesia	mm	2.5	2.5	2.5	2.5	2.5
Dimensionet (GJxThxL)	E jashtme	mm	1463x756x300	1500x1000x500			1700x1100x650
	Paketimi	mm	1514x785x360	1840x1200x673			1890x1460x835
Pesha neto/ bruto		kg	63.5/71	130/182	134/188	134/188	208/266
Ngarkesa	40'GP	set	84.0	18.0	18.0	18.0	16.0
	40'HQ	set	98.0	18.0	18.0	18.0	16.0