



## Njesite Outdoor DC Inverter

| GMV5 Slim                             |           |         |                     |                     |                     |
|---------------------------------------|-----------|---------|---------------------|---------------------|---------------------|
| Modeli                                |           |         | GMV-H224WL/A-X      | GMV-H280WL/A-X      | GMV-H335WL/A-X      |
| Gama e kapacitetit                    |           | HP      | 8                   | 10                  | 12                  |
| Kapaciteti                            | Ftohje    | Kw      | 20                  | 28                  | 33.5                |
|                                       | Ngrohje   | kW      | 22                  | 31.5                | 37.5                |
| EER                                   |           | W/W     | 3.1                 | 2.97                | 3.04                |
| COP                                   |           | W/W     | 4.1                 | 3.66                | 3.6                 |
| Furnizimi me energji                  |           | Ph/V/Hz | 380-415~3Ph~50/60Hz | 380-415~3Ph~50/60Hz | 380-415~3Ph~50/60Hz |
| Intensiteti i rrymes                  |           | A       | 25                  | 25                  | 25                  |
| Konsumi i energjise                   | Ftohje    | kW      | 7.2                 | 9.4                 | 11                  |
|                                       | Ngrohje   | kW      | 6.1                 | 8.6                 | 10.4                |
| Nr. Max i Indooreve qe mund te lidhen |           | njesi   | 13                  | 17                  | 20                  |
| Volumi i ngarkeses se gazit           |           | kg      | 6                   | 7.5                 | 8                   |
| Niveli i presionit te zhurmes         |           | dB(A)   | 58                  | 60                  | 60                  |
| Lidhja e tubit                        | Likuid    | mm      | ø9.52               | ø12.7               | ø12.7               |
|                                       | Gaz       | mm      | ø19.05              | ø25.4               | ø25.4               |
| Dimensionet (LxGjxTh)                 | E jashtme | mm      | 940x320x1430        | 940x460x1615        | 940x460x1615        |
|                                       | Paketimi  | mm      | 1033x433x1580       | 1033x573x1765       | 1033x573x1765       |
| Pesha                                 |           | kg      | 144                 | 175                 | 185                 |

| Funksioni | Kushtet nominale operative (temperatura) |        |                |        | Gama e operimit (temperatura) |
|-----------|--|--------|----------------|--------|-------------------------------|
|           | Kushtet outdoor                          |        | Kushtet indoor |        | Kushtet outdoor DB(°C)        |
|           | DB(°C)                                   | WB(°C) | DB(°C)         | WB(°C) | GMV5 Slim                     |
| Ftohje    | 35                                       | 0      | 27             | 19     | -5~52                         |
| Ngrohje   | 7  | 6      | 20             | 0      | -20~27                        |