



Njesite Outdoor DC Inverter

## GMV5 Slim

Modeli			GMV-224WL/B-X <sup>2</sup>	GMV-280WL/B-X <sup>2</sup>	GMV-335WL/B-X <sup>2</sup>
Gama e kapacitetit		HP	8	10	12
Kapaciteti	Ftohje	Kw	22.4	28	33.5
	Ngrohje	kW	24	30	35
EER		W/W	3.1	2.97	3.04
COP		W/W	4.1	3.66	3.6
Furnizimi me energji		Ph/V/Hz	380-415~3Ph~50/60Hz		
Intensiteti i rrymes		A	20	25	32
Konsumi i energjise	Ftohje	kW	7.2	9.8	10.6
	Ngrohje	kW	6.1	8.6	10.2
Nr. Max i Indooreve qe mund te lidhen		njesi	13	17	20
Volumi i ngarkeses se gazit		kg	6	7.5	8
Niveli i presionit te zhurmes	ftohje	dB(A)	58	59	60
	ngrohje	dB(A)	59	61	61
Lidhja e tubit	Likuid	mm	ø9.52	ø9.52	ø12.7
	Gaz	mm	ø19.05	ø22	ø25.4
Dimensionet (LxGjxTh)	E jashtme	mm	940x320x1430	940x460x1615	940x460x1615
	Paketimi	mm	1038x433x1580	1038x578x1765	1038x578x1765
Pesha		kg	133/144	166/183	177/194

Funksioni	Kushtet nominale operative (temperatura)				Gama e operimit (temperatura)
	Kushtet e outdoor		Kushtet e indoor		Kushtet e outdoor DB(°C)
	DB(°C)	WB(°C)	DB(°C)	WB(°C)	
Ftohje	35	-	27	19	-5~52
Ngrohje	7	6	20	-	-20~27