

Kanalor 2 Rreshta/ Tipi standard										
Modeli			FP-34WA-K	FP-51WA-K	FP-68WA-K	FP-85WA-K	FP-102WA-K	FP-136WA-K	FP-170WA-K	FP-204WA-K
Volumi i fluksit te ajrit (H/M/L)		CFM	200/146/125	300/232/155	400/291/194	500/375/250	600/464/309	800/644/429	1000/750/500	1200/926/618
ESP		Pa	12	12	12	12	12	12	12	12
Kapaciteti	Ftohje/ Ngrohje	kW	1.8/3.05	2.8/4.4	3.6/5.5	4.5/7.0	5.5/8.9	7.35/11.0	9.2/14.0	11.0/17.0
Furnizimi me energji	Tipi	Ph/V/Hz	1/220-240/50	1/220-240/50	1/220-240/50	1/220-240/50	1/220-240/50	1/220-240/50	1/220-240/50	1/220-240/50
	Inputi	W	37	45	62	70	96	120	145	185
Sistemi i ujit	Volumi i fluksit te ujit	l/s	0.1	0.14	0.17	0.21	0.27	0.6	0.45	0.5
	Renia e presionit	kPa	12	21	16	23	36	38	38	40
		Ft·WG	4	7	5.3	7.7	12.0	12.7	12.7	13.3
Niveli i presionit te zhurmes		dB(A)	35	38	40	42	44	46	48	50
Dimensionet (Gj×Th×L)	E jashtme	mm	881×510×245	1011×510×245	1131×510×245	1211×510×245	1211×510×245	1761×510×245	1761×510×245	1761×510×245
	Paketimi	mm	900×560×275	1030×560×275	1150×560×275	1230×560×275	1230×560×275	1780×560×275	1780×560×275	1780×560×275
Pesha neto/ Pesha bruto		kg	14/17	15/19.5	16.5/21	18/22	19/24	28.5/35	34/39	35/40
Lidhja e tubit	Hyrja & dalja e ujit (dia. brendshem)	inch(mm)	ø 3/4							
	Shkarkimi i kondenses (dia. i jashtem)	inch(mm)	ø 3/4							
Sasia e ngarkeses	40'GP/40'HQ	set	448/490	447/482	344/386	316/355	316/355	220/247	220/247	220/247
Opsionale	Komande ne distance	—	Komande ne distance: WK-010PA-K; Komande me ekran LCD: WK-110PA0							
	Plenum me filter	—	HF31	HF32	HF33	HF34	HF34	HF36	HF36	HF36
	Plenum pa filter	—	HF41	HF42	HF43	HF44	HF44	HF46	HF46	HF46

Kanalor 2 Rreshta/ Tipi me ESP te larte										
Modeli			FP-34WAH-K	FP-51WAH-K	FP-68WAH-K	FP-85WAH-K	FP-102WAH-K	FP-136WAH-K	FP-170WAH-K	FP-204WAH-K
Volumi i fluksit te ajrit (H/M/L) ESP		CFM	200/146/125	300/232/155	400/291/194	500/375/250	600/464/309	800/644/429	1000/750/500	1200/926/618
		Pa	30	30	30	30	30	30	30	30
Kapaciteti	Ftohje/ Ngrohje	kW	1.8/3.05	2.8/4.4	3.6/5.5	4.5/7.0	5.5/8.9	7.35/11.0	9.2/14.0	11.0/17.0
Furnizimi me energji	Tipi	Ph/V/Hz	1/220-240/50	1/220-240/50	1/220-240/50	1/220-240/50	1/220-240/50	1/220-240/50	1/220-240/50	1/220-240/50
	Inputi	W	42	55	68	80	102	140	158	195
Sistemi i ujit	Volumi i fluksit te ujit	l/s	0.1	0.14	0.17	0.21	0.27	0.6	0.45	0.5
	Renia e presionit	kPa	12	21	16	23	36	38	38	40
		Ft·WG	4	7	5.3	7.7	12.0	12.7	12.7	13.3
Niveli i presionit te zhurmes		dB(A)	38	40	42	44	46	47	49	52
Dimensionet (Gj×Th×L)	E jashtme	mm	881×510×245	1011×510×245	1131×510×245	1211×510×245	1211×510×245	1761×510×245	1761×510×245	1761×510×245
	Paketimi	mm	900×560×275	1030×560×275	1150×560×275	1230×560×275	1230×560×275	1780×560×275	1780×560×275	1780×560×275
Pesha neto/ Pesha bruto		kg	14/17	15/19.5	16.5/21	18/22	19/24	28.5/35	34/39	35/40
Lidhja e tubit	Hyrja & dalja e ujit (dia. brendshem)	inch(mm)	ø 3/4							
	Shkarkimi i kondenses (dia. i jashtem)	inch(mm)	ø 3/4							
Sasia e ngarkeses	40'GP/40'HQ	set	448/490	447/482	344/386	316/355	316/355	220/247	220/247	220/247
Opsionale	Komande ne distance	—	Komande ne distance: WK-010PA-K; Komande me ekran LCD: WK-110PA0							
	Plenum me filter	—	HF31	HF32	HF33	HF34	HF34	HF36	HF36	HF36
	Plenum pa filter	—	HF41	HF42	HF43	HF44	HF44	HF46	HF46	HF46



Fan Coil

Kanalor 3 Reshta									
Modeli			FP-34WAS-R		FP-51WAS-R	FP-68WAS-R	FP-85WAS-R	FP-102WAS-R	FP-136WAS-R
Volumi i fluksit te ajrit (H/M/L)		CFM	200/146/125		300/232/155	400/291/194	500/375/250	600/464/309	800/644/429
ESP		Pa	30		30	30	30	30	30
Kapaciteti	Ftohje/ ngrohje	kW	2.19/3.29		3.37/5.06	4.28/6.42	5.04/7.56	6.46/9.7	8.17/10.9
Furnizimi me energji	Tipi	Ph/V/Hz	1/220-240/50		1/220-240/50	1/220-240/50	1/220-240/50	1/220-240/50	1/220-240/50
	Inputi	W	44		59	72	87	108	156
Sistemi i ujit	Volumi i fluksit te ujit	l/s	0.11		0.17	0.22	0.25	0.32	0.37
	Renia e presionit	kPa	10		15	25	30	40	20
		Ft·WG	3.3		5	8.4	10	13.3	6.7
Niveli i presionit te zhurmes		dB(A)	38		40	42	44	46	47
Dimensionet (Gj×Th×L)	E jashtme	mm	881×510×245		1011×510×245	1131×510×245	1211×510×245	1211×510×245	1761×510×245
	Paketimi	mm	900×560×275		1030×560×275	1150×560×275	1230×560×275	1230×560×275	1780×560×275
Pesha neto/ pesha bruto		kg	15/19		16/20.5	18/23	19.5/24.5	21/26	30/35
Lidhja e tubit	Hyrja & dalja e ujit (dia. brendshem)	inch(mm)	ø 3/4						
	Shkarkimi i kondenses (dia. jashtem)	inch(mm)	ø 3/4						
Sasia e ngarkeses	40'GP/40'HQ	set	448/490		392/434	344/386	316/355	268/301	220/247
Opsionale	Komande ne distance	—	Komande ne distance: WK-010PA-K; Komande me ekran LCD: WK-110PA0						
	Plenum me filter	—	HF31		HF32	HF33	HF34	HF35	HF36
	Plenum pa filter	—	HF41		HF42	HF43	HF44	HF45	HF46

Kanalor 3 Reshta																	
Modeli			FP-170WAS-R		FP-204WAS-R		FP-238WAS-R		FP-272WAS-R		FP-306WAS-R		FP-340WAS-R				
Volumi i fluksit te ajrit (H/M/L)			CFM	1000/750/500		1200/926/618		1400/971/729		1600/1235/868		1800/1006/674		2000/1400/812			
ESP			Pa	30		30		30		30		30		30			
Kapaciteti		Ftohje/ ngrohje	kW	11.4/18.2		12.2/18.6		12.4/19.5		13.5/21.3		16.0/24.8		17.0/26.1			
Furnizimi me energji			Tipi	Ph/V/Hz		1/220-240/50		1/220-240/50		1/220-240/50		1/220-240/50		1/220-240/50			
			Inputi	W		174		212		380		475		535		640	
Sistemi i ujit			Volumi i fluksit te ujit	l/s		0.55		0.57		0.57		0.64		0.74		0.79	
			Renia e presionit	kPa		38		45		21.9		27.9		37.5		41.2	
				Ft·WG		12.7		15		7.3		9.3		12.5		13.7	
Niveli i presionit te zhurmes			dB(A)	49		52		56		59		62		63			
Dimensionet (Gj×Th×L)		E jashtme	mm	1921x510x245		1921×510×245		1671×595×345		1671×595×345		1921×595×354		1921×595×3545			
		Paketimi	mm	1940x560x275		1940×560×275		1750×650×380		1750×650×380		1950×650×380		1950×650×380			
Pesha neto/ pesha bruto			kg	33/38.5		24/39.5		48/55		48/55		52/60		52/60			
Lidhja e tubit		Hyrja & dalja e ujit (dia. brendshem)	inch(mm)	ø 3/4													
		Shkarkimi i kondenses (dia. jashtem)	inch(mm)	ø 3/4													
Sasia e ngarkeses		40'GP/40'HQ	set	196/220		196/220		140/166		140/166		130/153		130/153			
Opsionale		Komande ne distance	—	Komande ne distance: WK-010PA-K; Komande me ekran LCD: WK-110PA0													
		Plenum pa filter	—	HF37		HF37		HF28		HF28		HF29		HF29			
		Plenum me filter	—	HF47		HF47		HF48		HF48		HF49		HF49			



Fan Coil

Kanalor 4 Rreshta								
Modeli			FP-34WAF-R	FP-51WAF-R	FP-68WAF-R	FP-85WAF-R	FP-102WAF-R	FP-136WAF-R
Volumi i fluksit te ajrit (H/M/L)		CFM	188/156/80	289/259/186	383/324/207	477/368/242	571/507/395	760/616/424
ESP		Pa	30	30	30	30	30	30
Kapaciteti	Ftohje/ ngrohje	kW	2.11/3.7	3.82/5.7	4.85/7.2	5.71/8.5	7.32/10.9	9.26/13.8
Furnizimi me energji	Tipi	Ph/V/Hz	1/220-240/50	1/220-240/50	1/220-240/50	1/220-240/50	1/220-240/50	1/220-240/50
	Inputi	W	44	59	80	87	108	156
Sistemi i ujit	Volumi i fluksit te ujit	l/s	0.11	0.19	0.24	0.31	0.35	0.43
		kPa	15	7.8	9.7	23.3	35.5	16.4
	Renia e presionit	Ft-WG	5	2.6	3.2	7.8	11.8	5.5
Niveli i presionit te zhurmes		dB(A)	40	42	44	47	49	50
Dimensionet (Gj×Th×L)	E jashtme	mm	881×510×245	1011×510×245	1131×510×245	1211×510×245	1211×510×245	1761×510×245
	Paketimi	mm	900×560×275	1030×560×275	1150×560×275	1230×560×275	1230×560×275	1780×560×275
Pesha neto/ pesha bruto		kg	14.4/18.9	17.2/21.9	19.2/24.1	20.5/25.6	23.2/28.7	34.2/40.5
Lidhja e tubit	Hyrja & dalja e ujit (dia. brendshem)	inch(mm)	ø 3/4					
	Shkarkimi i kondenses (dia. jashtem)	inch(mm)	ø 3/4					
Sasia e ngarkeses	40'GP/40'HQ	set	448/490	392/434	344/386	316/355	268/301	220/247
Opsionale	Komande ne distance	—	Komande ne distance: WK-010PA-K; Komande me ekran LCD: WK-110PA0					
	Plenum me filter	—	HF31	HF32	HF33	HF34	HF35	HF36
	Plenum pa filter	—	HF41	HF42	HF43	HF44	HF45	HF46

Kanalor 4 Rreshta								
Modeli			FP-170WAF-R	FP-204WAF-R	FP-238WAF-R	FP-272WAF-R	FP-306WAF-R	FP-340WAF-R
Volumi i fluksit te ajrit (H/M/L)		CFM	1000/750/500	1200/926/618	1400/971/729	1600/1235/868	1800/1006/674	2000/1400/812
ESP		Pa	30	30	30	30	30	30
Kapaciteti	Ftohje/ ngrohje	kW	11.4/18.2	12.2/18.6	14.2/21.4	16.0/24.0	18.7/28.1	19.8/29.7
Furnizimi me energji	Tipi	Ph/V/Hz	1/220-240/50	1/220-240/50	1/220-240/50	1/220-240/50	1/220-240/50	1/220-240/50
	Inputi	W	174	212	380	475	535	640
Sistemi i ujit	Volumi i fluksit te ujit	l/s	0.51	0.58	0.78	0.89	1.02	1.13
		kPa	23.9	31.5	29.2	21.7	26.2	32.5
	Renia e presionit	Ft-WG	8	10.5	9.7	7.2	8.7	10.8
Niveli i presionit te zhurmes		dB(A)	51	52	56	58	60	61
Dimensionet (Gj×Th×L)	E jashtme	mm	1921×510×245	1921×510×245	1671×595×345	1671×595×345	1921×595×354	1921×595×3545
	Paketimi	mm	1940×560×275	1940×560×275	1750×650×380	1750×650×380	1950×650×380	1950×650×380
Pesha neto/ pesha bruto		kg	37.5/44	37.5/44	52/60	52/605	59/66	59/66
Lidhja e tubit	Hyrja & dalja e ujit (dia. brendshem)	inch(mm)	ø 3/4					
	Shkarkimi i kondenses (dia. jashtem)	inch(mm)	ø 3/4					
Sasia e ngarkeses	40'GP/40'HQ	set	196/220	196/220	140/166	140/166	130/153	130/153
Opsionales	Komande ne distance	—	Komande ne distance: WK-010PA-K; Komande me ekran LCD: WK-110PA0					
	Plenum me filter	—	HF37	HF37	HF28	HF28	HF29	HF29
	Plenum pa filter	—	HF47	HF47	HF48	HF48	HF49	HF49



Fan Coil

Kanalor 3+1 Rreshta								
Modeli			FP-34WAT-R	FP-51WAT-R	FP-68WAT-R	FP-85WAT-R	FP-102WAT-R	FP-136WAT-R
Volumi i fluksit te ajrit (H/M/L)		CFM	188/156/80	289/259/186	383/324/207	477/368/242	571/507/395	760/616/424
ESP		Pa	30	30	30	30	30	30
Kapaciteti	Ftohje/ ngrohje	kW	1.95/1.76	3.07/2.49	3.88/3.17	4.55/3.83	5.82/4.85	7.35/6.69
Furnizmi me energji	Tipi	Ph/V/Hz	1/220-240/50	1/220-240/50	1/220-240/50	1/220-240/50	1/220-240/50	1/220-240/50
	Inputi	W	44	59	80	87	108	156
Sistemi i ujit	Volumi i fluksit te ujit	l/s	0.11	0.17	0.21	0.29	0.32	0.39
		kPa	10.6	23.3	18.2	38	56.5	16.8
		Ft-WG	3.5	7.8	6.1	12.7	18.8	5.6
Niveli i presionit te zhurmes		dB(A)	40	42	44	47	49	50
Dimensionet (Gj×Th×L)	E jashtme	mm	881×510×245	1011×510×245	1131×510×245	1211×510×245	1211×510×245	1761×510×245
	Paketimi	mm	900×560×275	1030×560×275	1150×560×275	1230×560×275	1230×560×275	1780×560×275
Pehsa neto/ pesha bruto		kg	14.4/18.9	17.2/21.9	19.2/24.1	20.5/25.6	23.2/28.7	34.2/40.5
Lidhja e tubit	Hyrja & dalja e ujit (dia. brendshem)	inch(mm)	ø 3/4					
	Shkarkimi i kondenses (dia. jashtem)	inch(mm)	ø 3/4					
Sasia e ngarkeses	40'GP/40'HQ	set	448/490	392/434	344/386	316/355	268/301	220/247
Opsionale	Komande ne distance	—	Komande ne distance: WK-010PA-K; Komande me ekran LCD: WK-110PA0					
	Plenum me filter	—	HF31	HF32	HF33	HF34	HF35	HF36
	Plenum pa filter	—	HF41	HF42	HF43	HF44	HF45	HF46

Kanalor 3+1 Rreshta								
Modeli			FP-170WAT-R	FP-204WAT-R	FP-238WAT-R	FP-272WAT-R	FP-306WAT-R	FP-340WAT-R
Volumi i fluksit te ajrit (H/M/L)		CFM	948/836/645	1043/786/754	1400/970/729	1600/1235/867	1800/1006/674	2000/1400/812
ESP		Pa	30	30	30	30	30	30
Kapaciteti	Ftohje/ ngrohje	kW	9.65/7	10.96/8.85	12.35/12.97	13.49/14.165	15.67/16.46	16.53/17.36
Furnizmi me energji	Tipi	Ph/V/Hz	1/220-240/50	1/220-240/50	1/220-240/50	1/220-240/50	1/220-240/50	1/220-240/50
	Inputi	W	174	212	380	475	535	640
Sistemi i ujit	Volumi i fluksit te ujit	l/s	0.50	0.52	0.59	0.65	0.8	0.84
	Renia e presionit	kPa	28	29.4	21.8	26.6	42.1	46.4
		Ft-WG	9.3	9.8	7.3	8.9	14	15.5
Niveli i presionit te zhurmes		dB(A)	51	52	56	58	60	61
Dimensionet (Gj×Th×L)	E jashtme	mm	1921x510x245	1921×510×245	1671×595×345	1671×595×345	1921×595×354	1921×595×3545
	Paketimi	mm	1940x560x275	1940×560×275	1750×650×380	1750×650×380	1950×650×380	1950×650×380
Pesha neto/ pesha bruto		kg	37.5/44	37.5/44	52/60	52/60	59/66	59/66
Lidhja e tubit	Hyrja & dalja e ujit (dia. brendshem)	inch(mm)	ø 3/4					
	Shkarkimi i kondenses (dia. jashtem)	inch(mm)	ø 3/4					
Sasia e ngarkeses	40'GP/40'HQ	set	196/220	196/220	140/166	140/166	130/153	130/153
Opsionale	Komande ne distance	—	Komande ne distance: WK-010PA-K; Komande me ekran LCD: WK-110PA0					
	Plenum me filter	—	HF37	HF37	HF28	HF28	HF29	HF29
	Plenum pa filter	—	HF47	HF47	HF48	HF48	HF49	HF49