



Fan Coil

Montim ne Mur						
Modeli			FP-34BA2/D-K	FP-51BA2/D-K	FP-68BA2/D-K	FP-85BA2/D-K
Volumi i fryrjes se ajrit (H/M/L)	CFM		212	324	400	500
	CFM		189	243	348	417
	CFM		166	216	313	363
ESP	Pa		0	0	0	0
Kapaciteti	Ftohje	kW	2.0	2.5	3.6	4.2
	Ngrohje	kW	2.7	3.2	4.6	5.4
Furnizimi me energji	Tipi	Ph/V/Hz	1/220-240/50	1/220-240/50	1/220-240/50	1/220-240/50
	Input	W	50	50	60	66
Sistemi i ujit	Volumi i fluksit te ujit	l/s	0.111	0.125	0.167	0.195
	Renia e presionit	kPa	20	36	53	70
		Ft WG	6.56	11.81	17.38	22.96
Niveli i presionit te zhurmes	dB(A)		35.0	40.0	43.0	48
Lidhja e tubit	Hyrja, dalja e ujit	inch (mm)	ø1/2 (12.7)	ø1/2 (12.7)	ø1/2 (12.7)	ø1/2 (12.7)
	Shkarkimi i kondenses	inch (mm)	ø5/8 (15.6)	ø5/8 (15.6)	ø5/8 (15.6)	ø5/8 (15.6)
Dimensionet (GjxThxL)	E jashtme	mm	845x180x275	845x180x275	940x200x298	940x200x298
	Paketimi	mm	915x255x355	915x255x355	1010x285x380	1010x285x380
Pesha neto/ pesha bruto	kg		11/14	11/14	13/17	13/17
Standarde	Komande wireless		YB1FA(XFAN)	YB1FA(XFAN)	YB1FA(XFAN)	YB1FA(XFAN)
Opsionale	Komande ne distance		Z4E351B	Z4E351B	Z4E351B	Z4E351B