



Split mural DC Inverter
Ecodesign



Bora						
Modeli	GWH09AAB-K6DNA4A		GWH12AAB-K6DNA4A	GWH18AAB-K6DNA4B	GWH24AAB-K6DNA4C	
Funksioni			Ftohje/ Ngrohje	Ftohje/ Ngrohje	Ftohje/ Ngrohje	Ftohje/ Ngrohje
Kapaciteti	Ftohje	W	9600	11600	17700	22000
	Ngrohje	W	11900	12500	18500	27900
Koeficienti SEER			6.1	6.1	6.1	6.3
Furnizimi me energji	Ph, V, Hz		1Ph, 220-240V, 50hz	1Ph, 220-240V, 50hz	1Ph, 220-240V, 50hz	1Ph, 220-240V, 50hz
Hyryja e energjisë	Ftohje	W	799	997	1600	1960
	Ngrohje	W	743	942	1450	1860
Klasa e energjisë	Ftohje	A	3.8	4.5	10.8	10.9
	Ngrohje	A	3.6	4.4	12	11.3
Volumi i fryrjes së ajrit	Indoor	m³/h	520	550	720	850
Njësia e brendshme						
Niveli i presionit të zhurmës	Indoor	dB(A)(SH/H/ML)	40/37/35/28	42/37/34/28	48/44/39/34	49/44/41/39
Dimensionet e jashtme	LxGjxTh	mm	773x250x1855	773x250x185	970x300x225	970x300x225
Dimensionet e paketimit	LxGjxTh	mm	822x322x255	822x322x255	1020x369x295	1020x369x295
Pesha neto/ Pesha bruto	Indoor	kg	9.5/10.5	9.5/10.5	13.5/16.5	13.5/ 16.5
Njësia e jashtme						
Niveli i presionit të zhurmës	Outdoor	dB(A)	60	62	63	68
Lidhja e tubit	Likuid	mm	1/4"	1/4"	1/4"	1/4"
	Gaz	mm	3/8"	3/8"	3/8"	5/8"
Dimensionet e jashtme	LxGjxTh	mm	776x540x320	842x596x320	899x596x378	955x700x396
Dimensionet e paketimit	LxGjxTh	mm	823x595x358	881x363x645	948x420x645	1029x548x750
Pesha neto/ Pesha bruto	Outdoor	kg	30/32	31/34	39/ 42	46/50