



Split Mural DC Inverter

Ecodesign

Lomo DC Inverter LCLH						
Model			GWH09QB-K3DNC4G	GWH12QC-K3DNC4G	GWH18QD-K3DNC4G	GWH24QE-K3DNC4G
Funksioni			Ftohje/Ngrohje	Ftohje/Ngrohje	Ftohje/Ngrohje	Ftohje/Ngrohje
Kapaciteti	Ftohje	Btu/h	9000	12000	17500	23000
	Ngrohje	Btu/h	9600	12500	18000	25000
SEER/SCOP/(A)/SCOP©		W/W	6.1/3.2	6.1/3.2	6.1/3.1	6.3/2.8
Klasa e energjise			A++/A+	A++/A+	A++/A+	A++/A+
Furnizimi me energji		Ph, V, Hz	1Ph, 220-240V, 50Hz	1Ph, 220-240V, 50Hz	1Ph, 220-240V, 50Hz	1Ph, 220-240V, 50Hz
Energjia ne hyrje	Ftohje	W	805	1084	1580	1875
	Ngrohje	W	755	989	1410	1945
Intensiteti i rrymes	Ftohje	A	6.3	6.9	10.9	16.42
	Ngrohje	A	6.9	7.3	11.5	16.86
Volumi i fryrjes se ajrit	Indoor	m³/h (SH/H/MH/ML/L/SL)	560	660	800	1150
Njesia e brendshme						
Niveli i presionit te zhurmes	Indoor	dB(A)(SH/H/MH/ML)	55/52/44/38	56/53/45/39	58/54/51/48	64/61/58/54
Dimensionet e jashtme	LxGjxTh	mm	790x275x200	845x289x209	970x300x224	1078x325x246
Dimensionet e paketimit	LxGjxTh	mm	866x367x271	921x379x281	1041x320x383	1148x413x350
Pesha	Indoor	kg	12	13	17	21
Njesia e jashtme						
Niveli i presionit te zhurmes	Outdoor	dB(A)	61	62	63	68
Lidhja e tubit	Gaz	mm	ø9.52	ø9.52	ø12	ø16
	Likuid	mm	ø6	ø6	ø6	ø6
Dimensionet e jashtme	LxGjxTh	mm	776x540x320	776x540x320	955x700x396	955x700x396
Dimensionet e paketimit	LxGjxTh	mm	823x358x595	823x358x595	1029x750x458	1029x750x458
Pesha	Outdoor	kg	31	32	50	60