



## Split Mural DC Inverter

Ecodesign

Lomo Economic Inverter						
Model			GWH09QB-K3DNA1A	GWH12QC-K3DNA1A	GWH18QD-K3DNA1A	GWH24QD-K3DNA1A
Funksioni			Ftohje/Ngrohje	Ftohje/Ngrohje	Ftohje/Ngrohje	Ftohje/Ngrohje
Kapaciteti	Ftohje	Btu/h	8900	12000	18000	22000
	Ngrohje	Btu/h	10200	13000	19790	23000
SEER/SCOP/(A)/SCOP©		W/W	5.6/3.8	9212	5.6/3.8	6.2/3.8
Klasa e energjise Ftohje/Ngr.(A)/Ngr.(W)Ngr.(			A/A	A/A	A+/A	A+/A
Furnizimi me energji		Ph, V, Hz	1Ph, 220-240V, 50Hz	1Ph, 220-240V, 50Hz	1Ph, 220-240V, 50Hz	1Ph, 220-240V, 50Hz
Energjia ne hyrje	Ftohje	W	860	1150	1625	1760
	Ngrohje	W	930	1100	1760	2360
Intensiteti i rrymes	Ftohje	A	6.3	6.3	10.9	14.35
	Ngrohje	A	6.9	6.9	11.5	18.45
Volumi i fryrjes se ajrit	Indoor	m³/h (SH/H/MH/ML/L/SL)	560	660	800	1150
<b>Njesia e brendshme</b>						
Niveli i presionit te zhurmes	Indoor	dB(A)(SH/H/MH/ML)	55/52/44/38	56/53/45/39	58/54/51/48	64/61/58/54
Dimensionet e jashtme	LxGjxTh	mm	790x275x200	845x289x209	970x300x224	1078x325x246
Dimensionet e paketimit	LxGjxTh	mm	866x367x271	921x379x281	1041x320x383	1148x413x350
Pesha	Indoor	kg	12	13	17	21
<b>Njesia e jashtme</b>						
Niveli i presionit te zhurmes	Outdoor	dB(A)	61	62	63	70
Lidhja e tubit	Gaz	mm	ø9.52	ø9.52	ø12.7	ø16
	Likuid	mm	ø6	ø6	ø6	ø6
Dimensionet e jashtme	LxGjxTh	mm	776x540x320	848x540x320	955x700x396	955x700x396
Dimensionet e paketimit	LxGjxTh	mm	823x358x595	881x595x363	1029x750x458	1029x750x458
Pesha	Outdoor	kg	31	34	51	60