



Super Slim Ducct Type Ecodesign

Model			GFH(09)EA-K3DNA1A/I	GFH(12)EA-K3DNA1A/I	GFH(18)EA-K3DNA1A/I	GFH(21)EA-K3DNA1A/I	GFH(24)EA-K3DNA1A/I
Capacity	Cooling	Btu/h	8530	11940	17060	20470	24230
	Heating	Btu/h	9550	13140	18770	22520	27300
Power supply		Ph/V/Hz	1Ph,220-240V,50Hz				
Air flow volume		m ³ /h	450	500	700	1000	1000
		CFM	265	324	412	589	588.5
Sound pressure level		dB(A)	37 / 31	39 / 32	41 /33	42/34	42/34
Connecting pipe	Gas	inch(mm)	3/8(∅9.52)	3/8(∅9.52)	1/2(∅12.7)	5/8(∅16)	5/8(∅16)
	Liquid	inch(mm)	1/4(∅6.35)	1/4(∅6.35)	1/4(∅6.35)	3/8(∅9.52)	3/8(∅9.52)
Dimension (WxDxH)	Outline	mm	700x615x200	700x615x200	900x615x200	1100X615X200	1100X615X200
	Package	mm	893x743x305	893x743x305	1123x743x305	1323X743X305	1323X743X305
Net weight/Gross weight		Kg	22/27	23/29	27/36	31/41	31/41