



Super Slim Ducct Type Ecodesign

Modeli			GFH(09)EA-K3DNA1A/I	GFH(12)EA-K3DNA1A/I	GFH(18)EA-K3DNA1A/I	GFH(21)EA-K3DNA1A/I	GFH(24)EA-K3DNA1A/I
Kapaciteti	Ftohje	Btu/h	8530	11940	17060	20470	24230
	Ngrrohje	Btu/h	9550	13140	18770	22520	27300
Furnizimi me energji		Ph/V/Hz	1Ph,220-240V,50Hz				
Volumi i fryrjes se ajrit	m <sup>3</sup> /h		450	500	700	1000	1000
	CFM		265	324	412	589	588.5
Niveli i presionit te zhurmes		dB(A)	37 / 31	39 / 32	41 / 33	42/34	42/34
Lidhja e tubave	Gas	inch(mm)	3/8(Ø9.52)	3/8(Ø9.52)	1/2(Ø12.7)	5/8(Ø16)	5/8(Ø16)
	Leng	inch(mm)	1/4(Ø6.35)	1/4(Ø6.35)	1/4(Ø6.35)	3/8(Ø9.52)	3/8(Ø9.52)
Dimensionet (LxGjxTh)	E jashtme	mm	700x615x200	700x615x200	900x615x200	1100X615X200	1100X615X200
	Paketimi	mm	893x743x305	893x743x305	1123x743x305	1323X743X305	1323X743X305
Pesha		Kg	22/27	23/29	27/36	31/41	31/41