



Super DC Inverter Wall Split  
Ecodesign

U-Crown							
Model		GWH09UB-K3DNA4F		GWH12UB-K3DNA4F		GWH18UC-K3DNA4F	
Function		Cooling/ Heating		Cooling/ Heating		Cooling/ Heating	
Capacity	Cooling	Btu/h	9000(1300~13600)	1200(1300~15200)	18000(3071~19619)		
	Heating	Btu/h	10200((1900~16400)	12300(1900~18400)	18000(2559~24737)		
Pdesignh(A)Pdesignh(W)Pdesignh©		Btu/h	9200/9600/9200	10200/11000/10200	17742/180832/21154		
SEER/SCOP/(A)/SCOP(W)SCOP©		W/W	7.5/4.6/5.1/3.8	7.0/4.6/5.1/3.8	6.1/4.0/4.0/3.1		
Energy class Cooling/Heat.(A)/Heat.(W)Heat.(C)			A++/A++/A+++/A	A++/A++/A+++/A	A++/A+/A+/B		
Power supply		Ph, V, Hz	1Ph, 220-240V, 50hz	1Ph, 220-240V, 50hz	1Ph, 220-240V, 50hz		
Power input	Cooling	W	600(95~1550)	920(95~1550)	1600(200~2050)		
	Heating	W	800(100~16300)	970(100~1680)	1420(200~2400)		
Rated current	Cooling	A	6.5	6.8	9.1		
	Heating	A	6.8	7.1	10.6		
Airflow volume	Indoor	m³/h (SH/H/ML)	650/530/400	720/550/420	850/750/600		
<b>Indoor unit</b>							
Sound pressure level	Indoor	dB(A)(SH/H/ML)	56/50/46	57/51/47	58/54/48/		
Outline dimension	WxDxH	mm	860X305X170	860x305x170	960x320x205		
Package dimension	WxDxH	mm	935X388X295	935x388x295	1043x403x333		
Weight	Indoor	kg	14	14	17		
<b>Outdoor unit</b>							
Sound pressure level	Outdoor	dB(A)	62	62	63		
Piping connection	Gas	mm	ø12	ø9.52	ø12		
	Liquid	mm	ø6	ø6	ø6		
Outline dimension	WxDxH	mm	899X596X378	899x596x378	955x700x396		
Package dimension	WxDxH	mm	948X645X420	948x645x420	1029x750x458		
Weight	Outdoor	kg	48	48	56		