



Wall-mounted

Modeli			GMV-N22G/A3A-K*	GMV-N28G/A3A-K*	GMV-36G/A3A-K*	GMV-N45G/A3A-K*	GMV-50G/A3A-K*	GMV-N56G/A3A-K*	GMV-N63G/A3A-K*	GMV-N71G/A3A-K*	
Kapaciteti	Ftohje	Kw	2.2	2.8	3.6	4.5	5.0	5.6	6.3	7.1	
	Ngrohje	Kw	2.5	3.2	4.0	5.0	5.8	6.3	7.0	7.5	
Furnizimi me energji		V/Ph/Hz	220~240/1/50								
Konsumi i energjise		W	50	50	60	60	60	70	70	70	
Volumi i fryrjes se ajrit		m ³ /h	500/420/350	500/420/350	630/550/480	630/550/480	630/550/480	750/600/500	750/600/500	750/600/500	
		CFM	294/247/206	294/247/206	371/324/282	371/324/282	371/324/282	441/353/294	441/353/294	441/353/294	
Rryma nominale	Ftohje	A	0.2	0.2	0.31	0.31	0.31	0.31	0.31	0.31	
	Ngrohje	A	0.2	0.2	0.31	0.31	0.31	0.31	0.31	0.31	
	Ngrohje uji	A	/	/	/	/	/	/	/	/	
Niveli i presionit te zhurmes		dB(A)	38/34/30	38/34/30	44/41/38	44/41/338	44/41/38	44/41/38	44/41/38	44/41/38	
Lidhja e tubit	Likuid	mm	ø6.35	ø6.35	ø6.35	ø6.35	ø6.35	ø9.52	ø9.52	ø9.52	
	Gaz	mm	ø9.52	ø9.52	ø12.7	ø12.7	ø12.7	ø15.9	ø15.9	ø15.9	
Tubi i shkarkimit	Dia. jashtem	mm	ø20	ø20	ø20	ø20	ø20	ø30	ø30	ø30	
	Trashesia	mm	1.5	1.5	1.5	1.5	1.5	1.5	1.5	1.5	
Dimensionet (GJxThxL)	E jashtme	mm	843x180x275			940x200x298			1008x221x319		
	Paketimi	mm	970x255x355			1068x285x380			1128x395x313		
Pesha neto/ bruto		kg	10/12.5	10/12.5	12.5/15.5	12.5/15.5	12.5/15.5	15/18.5	15/18.5	15/18.5	
Ngarkesa	40'GP	set	702	702	557	557	557	441	441	441	
	40'HQ	set	819	819	624	624	624	503	503	503	



Wall-mounted

Model			GMV-N22G/A3A-K*	GMV-N28G/A3A-K*	GMV-36G/A3A-K*	GMV-N45G/A3A-K*	GMV-50G/A3A-K*	GMV-N56G/A3A-K*	GMV-N63G/A3A-K*	GMV-N71G/A3A-K*	
Capacity	Cooling	Kw	2.2	2.8	3.6	4.5	5.0	5.6	6.3	7.1	
	Heating	Kw	2.5	3.2	4.0	5.0	5.8	6.3	7.0	7.5	
Power supply		V/Ph/Hz	220~240/1/50								
Power consumption		W	50	50	60	60	60	70	70	70	
Airflow volume		m ³ /h	500/420/350	500/420/350	630/550/480	630/550/480	630/550/480	750/600/500	750/600/500	750/600/500	
		CFM	294/247/206	294/247/206	371/324/282	371/324/282	371/324/282	441/353/294	441/353/294	441/353/294	
Rated current	Cooling	A	0.2	0.2	0.31	0.31	0.31	0.31	0.31	0.31	
	Heating	A	0.2	0.2	0.31	0.31	0.31	0.31	0.31	0.31	
	Water heating	A	/	/	/	/	/	/	/	/	
Sound pressure level		dB(A)	38/34/30	38/34/30	44/41/38	44/41/38	44/41/38	44/41/38	44/41/38	44/41/38	
Connecting pipe	Liquid	mm	ø6.35	ø6.35	ø6.35	ø6.35	ø6.35	ø9.52	ø9.52	ø9.52	
	Gas	mm	ø9.52	ø9.52	ø12.7	ø12.7	ø12.7	ø15.9	ø15.9	ø15.9	
Drain pipe	External dia.	mm	ø20	ø20	ø20	ø20	ø20	ø30	ø30	ø30	
	Thickness	mm	1.5	1.5	1.5	1.5	1.5	1.5	1.5	1.5	
Dimensions (WxDxH)	outline	mm	843x180x275			940x200x298			1008x221x319		
	package	mm	970x255x355			1068x285x380			1128x395x313		
Net weight/Gross weight		kg	10/12.5	10/12.5	12.5/15.5	12.5/15.5	12.5/15.5	15/18.5	15/18.5	15/18.5	
Loading quantity	40'GP	set	702	702	557	557	557	441	441	441	
	40'HQ	set	819	819	624	624	624	503	503	503	