



Floor Ceiling Indoor Unit

Model			GMV-ND28ZD/A-T	GMV-ND36ZD/A-T	GMV-ND50ZD/A-T	GMV-ND63ZD/A-T	GMV-ND71ZD/A-T	GMV-ND90ZD/A-T	GMV-ND112ZD/A-T	GMV-ND125ZD/A-T	GMV-ND140ZD/A-T
Capacity	Cooling	Kw	2.8	3.6	5.0	6.3	7.1	9.0	11.2	12.5	14.0
	Heating	Kw	3.2	4.0	5.6	7.1	8.0	10.0	12.5	14.0	16.0
Power supply		V/Ph/Hz	220~240/1/50 & 208~230/1/60								
Power consumption		W	40	40	50	75	75	140	160	160	160
Airflow volume		m ³ /h	650/580/500	650/580/500	950/850/700	1400/1150/1000	1400/1150/1000	1600/1400/1200	2000/1800/1450	2000/1800/1450	2000/1800/1450
		CFM	380/341/294	380/341/294	560/500/410	825/677/590	825/677/590	940/824/706	1175/1059/853	1175/1059/853	1175/1059/853
Rated current	Cooling	A	0.2	0.2	0.25	0.38	0.38	0.7	0.95	0.95	0.95
	Heating	A	0.2	0.2	0.25	0.38	0.38	0.7	0.95	0.95	0.95
	Water heating	A	/	/	/	/	/	/	/	/	/
Sound pressure level		dB(A)	36/34/32	36/34/32	42/38/33	44/42/39	44/42/39	50/47/43	51/47/42	52/49/45	52/49/45
Connecting pipe	Liquid	mm	ø6.35	ø6.35	ø6.35	ø9.52	ø9.52	ø9.52	ø9.52	ø9.52	ø9.52
	Gas	mm	ø9.52	ø12.7	ø12.7	ø15.9	ø15.9	ø15.9	ø15.9	ø15.9	ø15.9
Drain pipe	External dia.	mm	ø17	ø17	ø17	ø17	ø17	ø17	ø17	ø17	ø17
	Thickness	mm	1.75	1.75	1.75	1.75	1.75	1.75	1.75	1.75	1.75
Dimensions (WxDxH)	outline	mm	1220x700x225			1420x700x245			1700x700x245		
	package	mm	1343x823x315			1548x828x315			1828x828x345		
Net weight/Gross weight		kg	40/49	40/49	40/49	50/58	50/58	50/58	60/68	60/68	60/68
Loading quantity	40'GP	set	145	145	145	90	90	90	84	84	84
	40'HQ	set	158	158	158	98	98	98	98	98	98