



Sunny Dehumidifier

Model			GDN10AH-K4EBB2C	GDN12AH-K4EBB2C	GDN16AH-K4EBB2C	GDN20AH-K4EBB2C	GDN24AH-K4EBB2C	GDN30AI-K4EBB3G
Volumi I heqjes se lageshtires		L/D	10	12	16	20	24	30
Furnizimi me energji		Ph,V,Hz	1Ph,220-240V,50Hz					
Hyrja e energjise		W	250	250	300	330	330	500
Klasa e energjise		A	1.2	1.2	1.35	1.5	1.5	2.5
volumi I nxjerrjes se ajrit		m ³ h (H/M/L)	150/120/100	150/120/100	180/160/140	180/160/140	180/160/140	3000/250/220
Niveli I presionit te zhurmes		db(A)(H/M/L)	43/41/39	43/41/39	45/43/41	45/43/41	47/45/43	48/45/42
Volumi I rezervuarit te ujit		L	4.0/4.6	4.0/4.6	4.0/4.6	4.0/4.6	4.0/4.6	7/8.3
Dimensioni	I jashtem	mm	343x5225x262	343x525x262	343x525x262	343x525x262	343x525x262	383x611x298
	Paketimi	mm	394x584x313	394x584x313	394x584x313	394x584x313	394x584x313	440x346x655
Menyra e operimit			elektronik	elektronik	elektronik	elektronik	elektronik	elektronik
Pesha Neto/ Pesha bruto		Kg	13/14.5	13/14.5	15.0/17.0	15.5/17.0	16.0/17.0	18/20

Model			GDN10AH-K4EBB2C	GDN12AH-K4EBB2C	GDN16AH-K4EBB2C	GDN20AH-K4EBB2C	GDN24AH-K4EBB2C	GDN30AI-K4EBB3G
Dehumidifying volume		L/D	10	12	16	20	24	30
Power supply		Ph,V,Hz	1Ph,220-240V,50Hz					
Power input		W	250	250	300	330	330	500
Rated current		A	1.2	1.2	1.35	1.5	1.5	2.5
Airflow olume		m ³ h (H/M/L)	150/120/100	150/120/100	180/160/140	180/160/140	180/160/140	3000/250/220
Sound prower level		db(A)(H/M/L)	43/41/39	43/41/39	45/43/41	45/43/41	47/45/43	48/45/42
Water tank volume		L	4.0/4.6	4.0/4.6	4.0/4.6	4.0/4.6	4.0/4.6	7/8.3
Dimensions (WxDxH)	outline	mm	343x5225x262	343x525x262	343x525x262	343x525x262	343x525x262	383x611x298
	package	mm	394x584x313	394x584x313	394x584x313	394x584x313	394x584x313	440x346x655
Operation mode			electronic	electronic	electronic	electronic	electronic	electronic
Net weight/Gross weight		Kg	13/14.5	13/14.5	15.0/17.0	15.5/17.0	16.0/17.0	18/20