



Njesite Outdoor

Chiller Modular Ajer-Uje						
Modeli	Pompe nxehtesie		LSQWRF65M/NaD-M	LSQWRF80M/NaD-M	LSQWRF130M/NaD-M	LSQWRF160M/NaD-M
Kapaciteti	Ftohje	kW	60	71	120	145
	Ngrohje	kW	65	79.5	130	170
Hapat e kapacitetit		%	0-50%-100%		0-25%-50%-75%-100%	
EER/COP		W/W	2.84/3.09	2.76/2.94	2.84/2.93	2.74/3.04
Furnizimi me energji		Ph/V/Hz	380-415V, 3Ph~50Hz			
Fuqia ne hyrje	Ftohje	kW	21.1	25.7	42.3	53
	Ngrohje	kW	21	27	44.4	56
Kompresori	Tipi		Shpejtesi konstante rrotullimi			
	Menyra e startit		Startim direkt			
	Sasia		2	2	4	4
Shkembyesi i nxehtesise pjesa e ujit	Tipi		Shkembyes nxehtesie me eficense te larte me bobine			
	Volumi i fluksit te ujit	L/s	2.87	3.39	5.73	6.92
		GPM	45	54	91	110
	Renia e presionit	kPa	15	20	30	35
		ft. WG	4.92	6.56	9.84	11.48
Lidhja e tubit		DN65		DN80		
Shkembyesi i nxehtesise pjesa e ajrit	Tipi		Tub alumini, fin-bakri			
	Tipi i ventilatorit		Fluks aksial	Fluks aksial	Fluks aksial	Fluks aksial
	Numri i ventilatoreve		2	2	4	4
	Volumi total i fluksit te ajrit	L/s	2x0.375x10 <sup>4</sup>	2x0.4167x10 <sup>4</sup>	4x0.375x10 <sup>4</sup>	4x0.4167x10 <sup>4</sup>
		CFM	2x0795x10 <sup>4</sup>	2x0.882x10 <sup>4</sup>	4x0795x10 <sup>4</sup>	4x0.882x10 <sup>4</sup>
Fuqia totale e motorit te helikes		kW	2x0.650	2x0.950	4x0.650	4x0.950
Niveli i presionit te zhurmes		dB(A)	70	71	72	74
Dimensionet (GjxThxL)	E jashtme	mm	2040x1000x2230	2040x1000x2230	2226x1650x2230	2226x1650x2230
	Paketimi	mm	2120x1080x2230	2120x1080x2230	2306x1730x2230	2306x1730x2230
Pesha neto/ bruto		kg	710/715	760/765	1256/1261	1440/1445