



## On/ off Wall Split Unit

Bora						
Model	GWH09AAA-K3NNA1A		GWH12AAB-K3NNA1A	GWH18AAC-K3NNA1A	GWH24AAD-K3NNA1A	
Function			Cooling/ Heating	Cooling/ Heating	Cooling/ Heating	Cooling/ Heating
Capacity	Cooling	W	8700	11000	16400	21000
	Heating	W	9100	11800	17100	22900
EER/ COP			3.1/3.45	3.21 /3.61	3.21/ 3.61	3.21/ 3.61
Power Supply	Ph, V, Hz		1Ph, 220-240V, 50hz	1Ph, 220-240V, 50hz	1Ph, 220-240V, 50hz	1Ph, 220-240V, 50hz
Power Input	Cooling	W	799	1012	1495	1915
	Heating	W	743	941	1500	1858
Rated Current	Cooling	A	3.7	4.3	6.8	8.49
	Heating	A	3.3	4.4	6.7	8.23
Aiflow Volume	Indoor	m³/h	470	550	660	900
<b>Indoor Unit</b>						
Sound pressure level	Indoor	dB(A)(SH/H/ML)	26/35/28/40	33/36/39/42	31/34/38/42	37/41/45/49
Outline Dimension	WxHxD	mm	698x250x185	773x250x185	849x540x320	970x300x225
Package Dimension	WxHxD	mm	747x322x255	822x322x255	902x357x279	1020x369x295
Net Weight/ Gross Weight	Indoor	kg	7.5/ 8.5	8.5/9.5	11/ 13	13.5/ 16.5
<b>Outdoor Unit</b>						
Sound pressure level	Outdoor	dB(A)	49	52	56	56
Piping Connection	Gas	mm	3.8"	1/2"	1/2"	1/2"
	Liquid	mm	1/4"	1/4"	1/4"	1/4"
Outline Dimension	WxHxD	mm	720x428x310	776x540x320	848x540x320	913x680x378
Package Dimension	WxHxD	mm	768x353x490	823x358x595	881x363x595	997x431x740
Net Weight/ Gross Weight	Outdoor	kg	24.5 /26.5	29/ 31.5	39/ 41.5	50/ 54