



Sunny							
Model		GDN10AH-K4EBB2C	GDN12AH-K4EBB2C	GDN16AH-K4EBB2C	GDN20AH-K4EBB2C	GDN24AH-K4EBB2C	GDN30AI-K4EBB3G
Dehumidifying volume	L/D	10	12	16	20	24	30
Power supply	Ph,V,Hz	1Ph,220-240V,50Hz					
Power input	W	250	250	300	330	330	500
Rated current	A	1.2	1.2	1.35	1.5	1.5	2.5
Airflow olume	m ³ h (H/M/L)	150/120/100	150/120/100	180/160/140	180/160/140	180/160/140	3000/250/220
Sound prower level	db(A)(H/M/L)	43/41/39	43/41/39	45/43/41	45/43/41	47/45/43	48/45/42
Water tank volume	L	4.0/4.6	4.0/4.6	4.0/4.6	4.0/4.6	4.0/4.6	7/8.3
Dimensions outline	mm	343x5225x262	343x525x262	343x525x262	343x525x262	343x525x262	383x611x298
Dimensions package	mm	394x584x313	394x584x313	394x584x313	394x584x313	394x584x313	440x346x655
Operation mode		electronic	electronic	electronic	electronic	electronic	electronic
Net weight/Gross weight	Kg	13/14.5	13/14.5	15.0/17.0	15.5/17.0	16.0/17.0	18/20