



Njesite Outdoor DC Inverter

GMV 5											
Modeli		GMV-224WM/B-X	GMV-280WM/B-X	GMV-335WM/B-X	GMV-400WM/B-X	GMV-450WM/B-X	GMV-504WM/B-X	GMV-560WM/B-X	GMV-615WM/B-X		
Gama e kapacitetit		HP	8	10	12	14	16	18	20	22	
Kapaciteti	Ftohje	Kw	22.4	28	33.5	40	45	50.4	56	61.5	
	Ngrohje	kW	25	31.5	37.5	45	50	56	63	69	
EER		W/W	4.31	4	3.98	3.76	3.56	3.55	3.5	3.32	
COP		W/W	4.55	4.32	4.17	4.05	3.85	4.01	3.8	3.65	
Furnizimi me energji		Ph/V/Hz	380~415V-3Ph-50/60Hz								
Intensiteti i rrymes		A	15.7/20	20.9/25	24.7/32	28.8/40	33.2/40	44.7/5	50/63	52/63	
Konsumi i energjise	Ftohje	kW	5.2	7	8.41	10.65	12.65	14.2	16	18.5	
	Ngrohje	kW	5.5	7.3	9	11.1	13	14.1	16.6	18.9	
Nr. Max i Indooreve qe mund te lidhen		njesi	13	16	19	23	26	29	32	35	
Volumi i ngarkeses se gazit		Kg	5.9	6.7	8.2	9.8	10.3	11.3	14.3	14.3	
Niveli i presionit te zhurmes		dB(A)	60	61	63	63	63	63	63	64	
Lidhja e tubit	Likuid	inch(mm)	ø9.52		ø12.7			ø15.9			
	Gaz (presion i	inch(mm)	ø19.05	ø22.2	ø25.4	ø25.4	ø28.6	ø28.6			
Dimensionet (LxGjxTh)	E jashtme	mm	930x765x1605		1340x765x1605			1340x765x1740			
	Paketimi	mm	1010x840x1775		1420x840x1775			1420x840x1910			
Pesha		Kg	225/235	225/235	285/300	360/375	360/375	360/375	385/400	385/400	

Funksioni	Kushtet nominale operative (temperatura)				Gama e operimit (temperatura)
	Kushtet outdoor		Kushtet indoor		Kushtet e outdoor DB(°C)
	DB(°C)	WB(°C)	DB(°C)	WB(°C)	
Ftohje	35	-	27	19	-5~52
Ngrohje	7	6	20	-	-20~24