



Fan Coil

2 Rows/ Standard Type											
Model			FP-34WA-K	FP-51WA-K	FP-68WA-K	FP-85WA-K	FP-102WA-K	FP-136WA-K	FP-170WA-K	FP-204WA-K	
Air flow volume(H/M/L)	CFM		200/146/125	300/232/155	400/291/194	500/375/250	600/464/309	800/644/429	1000/750/500	1200/926/618	
	Pa		12	12	12	12	12	12	12	12	
ESP											
Capacity	Cooling/Heating	kW	1.8/3.05	2.8/4.4	3.6/5.5	4.5/7.0	5.5/8.9	7.35/11.0	9.2/14.0	11.0/17.0	
	Type	Ph/V/Hz	1/220-240/50	1/220-240/50	1/220-240/50	1/220-240/50	1/220-240/50	1/220-240/50	1/220-240/50	1/220-240/50	
Power system	Input	W	37	45	62	70	96	120	145	185	
	Water flow volume	l/s	0.1	0.14	0.17	0.21	0.27	0.6	0.45	0.5	
Water system	Pressure drop	kPa	12	21	16	23	36	38	38	40	
		Ft.WG	4	7	5.3	7.7	12.0	12.7	12.7	13.3	
Sound pressure level		dB(A)	35	38	40	42	44	46	48	50	
Dimension (W×D×H)	Outline	mm	881×510×245	1011×510×245	1131×510×245	1211×510×245	1211×510×245	1761×510×245	1761×510×245	1761×510×245	
	Package	mm	900×560×275	1030×560×275	1150×560×275	1230×560×275	1230×560×275	1780×560×275	1780×560×275	1780×560×275	
Net weight/Gross weight		kg	14/17	15/19.5	16.5/21	18/22	19/24	28.5/35	34/39	35/40	
Connection pipe diameter	Water inlet & outlet (inner groove)	inch(mm)								Rc3/4	
	Condensed water drain (outer groove)	inch(mm)								Rc3/4	
Loading quantity	40'GP/40'HQ	set	448/490	447/482	344/386	316/355	316/355	220/247	220/247	220/247	
Optionals	Wired remote controller	—	Luxury wired controller: WK-010PA-K; LCD controller: WK-110PA0								
	Plenum with filter	—	HF31	HF32	HF33	HF34	HF34	HF36	HF36	HF36	
	Plenum without filter	—	HF41	HF42	HF43	HF44	HF44	HF46	HF46	HF46	

2 Rows/ High ESP Type											
Model			FP-34WAH-K	FP-51WAH-K	FP-68WAH-K	FP-85WAH-K	FP-102WAH-K	FP-136WAH-K	FP-170WAH-K	FP-204WAH-K	
Air flow volume(H/M/L)	CFM		200/146/125	300/232/155	400/291/194	500/375/250	600/464/309	800/644/429	1000/750/500	1200/926/618	
	Pa		30	30	30	30	30	30	30	30	
ESP											
Capacity	Cooling/Heating	kW	1.8/3.05	2.8/4.4	3.6/5.5	4.5/7.0	5.5/8.9	7.35/11.0	9.2/14.0	11.0/17.0	
	Type	Ph/V/Hz	1/220-240/50	1/220-240/50	1/220-240/50	1/220-240/50	1/220-240/50	1/220-240/50	1/220-240/50	1/220-240/50	
Power system	Input	W	42	55	68	80	102	140	158	195	
	Water flow volume	l/s	0.1	0.14	0.17	0.21	0.27	0.6	0.45	0.5	
Water system	Pressure drop	kPa	12	21	16	23	36	38	38	40	
		Ft.WG	4	7	5.3	7.7	12.0	12.7	12.7	13.3	
Sound pressure level		dB(A)	38	40	42	44	46	47	49	52	
Dimension (W×D×H)	Outline	mm	881×510×245	1011×510×245	1131×510×245	1211×510×245	1211×510×245	1761×510×245	1761×510×245	1761×510×245	
	Package	mm	900×560×275	1030×560×275	1150×560×275	1230×560×275	1230×560×275	1780×560×275	1780×560×275	1780×560×275	
Net weight/Gross weight		kg	14/17	15/19.5	16.5/21	18/22	19/24	28.5/35	34/39	35/40	
Connection pipe diameter	Water inlet outlet(inner groove)inch(mm)									Rc3/4	
	Condensed water drain (outer groove)	inch(mm)								Rc3/4	
Loading quantity	40'GP/40'HQ	set	448/490	447/482	344/386	316/355	316/355	220/247	220/247	220/247	
Optionals	Wired remote controller	—	Luxury wired controller: WK-010PA-K; LCD controller: WK-110PA0								
	Plenum with filter	—	HF31	HF32	HF33	HF34	HF34	HF36	HF36	HF36	
	Plenum without filter	—	HF41	HF42	HF43	HF44	HF44	HF46	HF46	HF46	



Fan Coil

3 Rows								
Model			FP-34WAG!F	FP-51WAG!F	FP-68WAG!F	FP-85WAG!F	FP-102WAG!F	FP-136WAG!F
Air flow volume(H/M/L)		CFM	200/146/125	300/232/155	400/291/194	500/375/250	600/464/309	800/644/429
ESP		Pa	H€	H€	H€	H€	H€	H€
Capacity	Cooling/Heating	kW	G€FJĐH€GJ	H€HĪĐĪ€Ī	I€GĪĐĪ€IG	Ī€€ĪĐĪ€ĪĪ	Ī€ĪĐJ€Ī	Ī€FĪĐF€€J
	Type	Ph/V/Hz	1/220-240/50	1/220-240/50	1/220-240/50	1/220-240/50	1/220-240/50	1/220-240/50
Power system	Input	W	I I	Ī J	Ī G	Ī Ī	F€ Ī	1 Ī Ī
	Water flow volume	l/s	0.F1	0.1Ī	0.GG	0.2Ī	0.HG	0.HĪ
Water system	Pressure drop	kPa	1€	F Ī	G Ī	H€	I€	G€
		Ft.WG	H€H	Ī	Ī€Ī	F€	1H€H	Ī€Ī
Sound pressure level		dB(A)	3Ī	I€	4G	4I	4Ī	4Ī
Dimension (W×D×H)	Outline	mm	881×510×245	1011×510×245	1131×510×245	1211×510×245	1211×510×245	1761×510×245
	Package	mm	900×560×275	1030×560×275	1150×560×275	1230×560×275	1230×560×275	1780×560×275
Net weight/Gross weight		kg	1 Ī Đ FJ	1 Ī Đ G€ Ī	1 Ī Đ GH	FJ€ Ī Đ G Ī € Ī	G F Đ G Ī	H€ Đ H Ī
Connection pipe diameter	Water inlet&outlet(inner groove)	inch(mm)	Rc3/4					
	Condensed water drain (outer groove)	inch(mm)	Rc3/4					
Loading quantity	40'GP/40'HQ	set	448/490	HJGĐ Ī H Ī	344/386	316/355	G Ī Ī Đ H€ F	220/247
Optionals	Wired remote controller	—	Luxury wired controller: WK-010PA-K; LCD controller: WK-110PA0					
	Plenum with filter	—	HF31	HF32	HF33	HF34	HF3 Ī	HF36
	Plenum without filter	—	HF41	HF42	HF43	HF44	HF4 Ī	HF46

3 Rows								
Model			FP-+%\$WAG!F	FP-&\$ (WAG!F	FP-&'8WAG!F	FP-&+&WAG!F	FP-'\$*WAG!F	FP-' (\$WAG!F
Air flow volume(H/M/L)		CFM	F€€€ĪĪ€Ī€€	FG€€JGĪĐĪFĪ	F400/JĪ1/ĪGJ	FĪ€€F€GHĪĐĪĪ	FĪ€€F€€ĪĐĪĪ	G€€€FĪ€€ĪFG
ESP		Pa	H€	H€	H€	H€	H€	H€
Capacity	Cooling/Heating	kW	FF€ĐĐFĪ€G	FG€GĐFĪ€Ī	FG€ĪĐFJ€Ī	FH€ĪĐGF€H	FĪ€€GĪ€Ī	FĪ€€GĪ€F
	Type	Ph/V/Hz	1/220-240/50	1/220-240/50	1/220-240/50	1/220-240/50	1/220-240/50	1/220-240/50
Power system	Input	W	F Ī Ī	GFG	H Ī €	I Ī Ī	Ī H Ī	Ī I €
	Water flow volume	l/s	0.Ī Ī	0.Ī Ī	0.Ī Ī	0.Ī Ī	0.Ī Ī	0.Ī J
Water system	Pressure drop	kPa	H Ī	I Ī	GF€J	GĪ€J	HĪ€Ī	I F€G
		Ft.WG	FG€Ī	F Ī	Ī.3	J€H	12.Ī	1H€Ī
Sound pressure level		dB(A)	I J	Ī G	Ī Ī	Ī J	Ī G	Ī H
Dimension (W×D×H)	Outline	mm	FJGF€ĪF€G Ī Ī	1JGFx510x245	1ĪĪ1x5ĪĪxH45	1ĪĪFx5ĪĪxH45	1JGFx5ĪĪxHĪĪ	1JG1x5ĪĪxHĪĪ15
	Package	mm	FJĪ€€ĪĪ€GĪĪ	1JĪ€x560x275	1Ī50xĪĪ0xHĪ€	1ĪĪ0xĪĪ0xHĪ€	FJĪ€xĪĪ€xHĪ€	1JĪ0xĪĪ0xHĪ€
Net weight/Gross weight		kg	HĐĐHĪ€Ī	GĪĐHJ€Ī	IĐĪĪ	IĐĪĪ	ĪGĐĪ€	ĪGĐĪ€
Connection pipe diameter	Water inlet&outlet(inner groove)	inch(mm)	Rc3/4					
	Condensed water drain (outer groove)	inch(mm)	Rc3/4					
Loading quantity	40'GP/40'HQ	set	FJĪĐGG€	FJĪĐGG€	FĪ€FĪĪ	FĪ€FĪĪ	FH€FĪH	FH€FĪH
Optionals	Wired remote controller	—	Luxury wired controller: WK-010PA-K; LCD controller: WK-110PA0					
	Plenum with filter	—	HF3Ī	HF3Ī	HFGĪ	HFGĪ	HFGJ	HFGJ
	Plenum without filter	—	HF4Ī	HF4Ī	HF4Ī	HFĪĪ	HF4J	HF4J